



Peterbilt Illinois-Joliet (P128)  
535 East S. Frontage Rd  
Bolingbrook, Illinois 60440

VILLAGE OF OAK PARK  
201 SOUTH BLVD OAK PARK IL 60302  
OAK PARK, Illinois 60302  
United States of America

Darren Simon  
Cell Phone: 815-375-1490  
Office Phone: (630)516-3560  
Email: dsimon@jxe.com

KEN CROWLEY

## Vehicle Summary

Unit		Chassis	
Model:	Model 567 Electric Vehicle	Fr Axle Load (lbs):	14600
Type:	Tractor	Rr Axle Load (lbs):	40000
Description 1:	567 EV rev 4	G.C.W. (lbs):	82000
Description 2:	1126PL		
Application		Road Conditions:	
Intended Serv.:	Construction Dump - On/Off Highway	Class A (Highway)	100
Commodity:	Construction Materials	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:		Wheelbase (in):	206
Length (ft):	0	Overhang (in):	55
Height (ft):	0	Fr Axle to BOC (in):	68.2
Max Laden Weight (lbs):	0		
Trailer		Cab to Axle (in):	137.8
No. of Trailer Axles:	2	Cab to EOF (in):	192.8
Type:	Semi-End Dump	Overall Comb. Length (in):	889.23
Length (ft):	53	Special Req.	
Height (ft):	13.5		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	Weight
<b>Base Model</b>			
0005672	O	<b>Model 567 Electric Vehicle</b> Rugged. Reliable. Rewarding. Electrified. The Model 567EV brings electric innovation to the vocational market. The PACCAR ePowertrain creates an adaptable platform for many applications. The 567EV can be configured to any wheelbase 190 or longer and allows for set forward or set back front axle locations. Two furnished by owner ePTO options, factory PTO controls and standard body builder lighting connections ensure any body is seamlessly integrated. Four distinct battery options allow for balancing weight, space and range with range up to 250 miles.	18,470
0091070	O	<b>Construction Materials</b>	0
0093060	O	<b>Construction Dump - On/Off Highway</b> Truck or tractor without liftable trailing axle which carries bulk materials (excavated earth, sand/gravel, asphalt, demolition debris, etc.) and unloads by dumping out the back, over the side of the body, or out the bottom of the trailer.	0
0096110	O	<b>Semi-End Dump</b>	0
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0
<b>Configuration</b>			
0200634	S	<b>Electric Vehicle</b>	0
0200700	O	<b>Not Applicable</b> Secondary Manufacturer	0
<b>Frame &amp; Equipment</b>			
0519180	S	<b>11-5/8" Steel Rails to 444"</b> 11.625 x 3.874 x .375 Dimension, 2,568,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 21.4 cubic inches. Weight: 1.91 lbs/inch pair	61
0611250	O	<b>Heavy-Duty Iron Front Spring Brackets</b> With Front Air Leaf the front spring bracket is iron but not the shackle bracket	35
0611330	O	<b>Zinc Coated Anti Corrosion Treated Frame Rails</b> Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	4
0611790	S	<b>Aluminum Frame Rail Crossmembers</b> Excludes suspension	0
0644000	S	<b>EOF Tractor Tapered with Crossmember</b> Includes Kingpin Cutout	0
0651010	S	<b>Peterbilt Rear Mudflaps and Straight Hangers</b>	0

Price Level: January 1, 2026

100% Complete

Date: January 22, 2026

Deal: 567 EV rev 4

Quote Number: QUO-1181916-V8T5Y3

Printed On: 1/21/2026 6:11:52 PM



Sales Code	Std/ Opt	Description	Weight
		Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	
0712520	O	<b>Holland (2) TH-10050 Tow Hooks EOF</b>	40
0854110	O	<b>JOST JSK37 Fifth Wheel Top Plate</b> The JOST JSK37U fifth wheel is a cast model suitable for a wide range of applications.	240
0870000		<b>Rear Or Fixd Setting Centerline Bogie</b>	0
0890090	O	<b>LH Fifth Wheel Release</b>	0
0890550	O	<b>7.6in - 8in Fifth Wheel Height</b>	0
0890660	O	<b>Outboard Fifth Wheel Mounting</b> Outboard mount is low-weight, no welding modular base design, offers weight savings with easy height change. Air Slide Only.	62
0890670	O	<b>No-Tilt Convertible</b> Jost air slide fifth wheel requires code 0890660 outboard IPO inboard.	24
0890830	O	<b>48" Air Slide</b>	265
0898030	O	<b>Fifth Wheel Slide Controls</b> Provided with Speed Interlock to prevent accidental activation above 7 MPH. Configurable from 5 to 10 MPH. Required with sliding Fifth Wheels.	2
0960000	O	<b>Frame Mounted Deckplate And Access Pkg, LH Side</b>	41
0960040	O	<b>Extended Deckplate Rearward To Fifth Wheel</b>	10
<b>Front Axle &amp; Equipment</b>			
1012330	S	<b>Meritor MFS+14F 14,600 Lb, 3.5" Drop</b>	0
1112150	S	<b>Taper Leaf Springs, Shocks 14,600 lb</b> Hendrickson Taper Leaf Springs, shocks 14,6000 lb.	0
1243060	S	<b>Power Steering Sheppard SD110</b> The SD110 power steering gear is a compact version of the M110 power steering gear. The SD110, working with a 185 bar pump is capable of steering vocational and heavy haul vehicles with front axle ratings of 13,200 to 16,000 lbs. in single gear applications.	0
1250185	S	<b>Power Steering Reservoir, PCAS Mounted</b>	0
1354850	O	<b>PHP10 Iron PreSet PLUS Hubs - Air Disc</b> Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	42

Price Level: January 1, 2026

Deal: 567 EV rev 4

Printed On: 1/21/2026 6:11:52 PM

100% Complete

Date: January 22, 2026

Quote Number: QUO-1181916-V8T5Y3



Sales Code	Std/ Opt	Description	Weight
1380070	O	<b>Greasable Front Spring Pins</b>	0
1380290	S	<b>Bendix Air Disc Front Brakes</b> Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0
1380380	S	<b>Tenneco Shocks For Steer Axle</b> Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0
1380470	O	<b>Meritor Wide Track IPO Standard, Front Axle</b> Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	15
1391480	O	<b>Pad Dust Shields for Air Disc Brakes; Front Axle</b> Pad dust shields for air disc brakes can increase brake life. Brake dust shields reduce the buildup of road grime, extend brake system life and prevent premature failure.	2
<b>Rear Axle &amp; Equipment</b>			
1521630	O	<b>Meritor RT40-160 40,000 lb</b>	500
1616295	S	<b>PHP10 Aluminum Preset PLUS Hubs - Air Disc</b>	0
1680390	S	<b>Bendix ESP Electronic Stability Program With ATC</b> Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0
1682420	O	<b>ISO 3731 Connector with Trailer ABS Power on Pin7</b> Mounted adjacent to J560 Trailer Connector. This option is required, and only available, with any option related to J560 7th wire functionality.	9
1682710	S	<b>Anti-Lock Braking System (ABS) 6S6M</b> ABS-6. Includes air braking system.	0
1683245	S	<b>Tire Pressure Monitoring System</b>	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
1687040	O	<b>Air Disc Rear Brakes, Tandem Drive Axle</b> Includes Automatic Slack Adjusters.	0
1687090	O	<b>Diff Lock Tandem Axles</b> With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.	60

Price Level: January 1, 2026

100% Complete

Date: January 22, 2026

Deal: 567 EV rev 4

Quote Number: QUO-1181916-V8T5Y3

Printed On: 1/21/2026 6:11:52 PM



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
1687095	O	<b>Diff Lock Auto Disengagement</b> With Speed Interlock	<b>0</b>
1703730	O	<b>Ratio 3.73 Rear Axle</b>	<b>0</b>
1824430	O	<b>Hendrickson HMX EX 400, 40,000 LBS., 52"</b> Haulmaax, 60K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.	<b>167</b>
1921365	O	<b>15.5" Saddle Height HMX EX 400/460</b> IPO Std 18.5"	<b>0</b>
<b>Engine &amp; Equipment</b>			
2062370	S	<b>EMotor 470HP Peak (365 Cont) 1850 lb-ft</b> Midship Elec Drive Motor	<b>0</b>
2091120	S	<b>EMUX Electronics Architecture</b>	<b>0</b>
2092014	S	<b>Typical Operating Speed 65 MPH</b>	<b>0</b>
2092033	S	<b>Powertrain Optimized for Balance</b> Best analysis for vehicles where service includes frequent start and stop cycles.	<b>0</b>
2140220	S	<b>CARB and EPA Engine Idling Not Required</b>	<b>0</b>
2140675	O	<b>Emission Warranty Exception</b>	<b>0</b>
2516090	O	<b>315 AMP 12V DC-DC Converters</b>	<b>0</b>
2534130	O	<b>Elec Vehicle Batt Sys: Paccar 375 KWHR</b> USABLE CAPACITY, LFP CHEM, Approximately 150 mile range	<b>2,370</b>
2534160	O	<b>DC Charge Speed 350 KW</b>	<b>0</b>
2538020	S	<b>2 PACCAR Premium 12V Dual Purpose Batt 1460 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	<b>0</b>
2539000	S	<b>ESS ENCLOSURE: SING MTD LH UND CAB</b>	<b>0</b>
2539001	S	<b>ESS ENCLOSURE: SING MTD RH UND CAB</b>	<b>0</b>
2539002	O	<b>ESS ENCLOSURE: SING MTD UND CAB BETWEEN RAILS</b>	<b>0</b>
2539943	S	<b>AC Charge Speed 19.2 kW</b>	<b>0</b>
2539945	S	<b>LH BOC Charge Port Location</b>	<b>0</b>
2720110	S	<b>12.4 CFM E-Air Compressor</b>	<b>0</b>
3360100	S	<b>Integrated Battery Grid Heater</b>	<b>0</b>

Price Level: January 1, 2026

100% Complete

Date: January 22, 2026

Deal: 567 EV rev 4

Quote Number: QUO-1181916-V8T5Y3

Printed On: 1/21/2026 6:11:52 PM



Sales Code	Std/ Opt	Description	Weight
BEV Only			
<b>Transmission &amp; Equipment</b>			
4055000	S	<b>EMotor Integrated Transmission</b> 3-SPEED, 1st-10:1, 2cnd 7.92:1, 3rd 3.25:1	0
4210870	O	<b>RPL20 Driveline Interaxle</b> Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanently lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	0
4211240	O	<b>RPL25 Driveline, Without Midship Bearing</b> Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	0
4233950	O	<b>Dash Switch; E-PTO Activation</b>	0
4252610	S	<b>Column Mounted Shifter RH Side</b>	0
<b>Air &amp; Trailer Equipment</b>			
4510230	S	<b>Bendix AD-HFI Smart Air Dryer, Heater</b> Coalescing filter	0
4520420	O	<b>Pull Cords All Air Tanks</b>	1
4540420	S	<b>Nylon Chassis Hose</b>	0
4541490	O	<b>Tractor Air System, Spring Brake Relay IPO QR-1C</b> Functions as a quick release valve for the emergency side of the spring brakes.	0
4543320	S	<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
4544030	O	<b>Pre-Trip Brake Inspection, Dash Mounted Knob</b> The Pre-trip brake inspection is a safety feature that is easily accessible on the dash via the MTD knob. This blue colored knob on the dash applies the service brakes allowing the driver to exit the vehicle and check brake stroke and lights prior to the trip.	0
4610920	S	<b>Self-Returning Brake Hand Valve</b> Dash mounted controls	0
4611275	O	<b>12' AE Lines Straight, 3 In 1, (2) 7-Way Plugs</b> BOC socket, without QCMS2	8
4611460	S	<b>AE Connections Mounted On LH Rail</b>	0

Price Level: January 1, 2026

Deal: 567 EV rev 4

Printed On: 1/21/2026 6:11:52 PM

100% Complete

Date: January 22, 2026

Quote Number: QUO-1181916-V8T5Y3



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
4611590	O	<b>Gladhands, Plug, &amp; ISO Holder Mounted BOC/BOS</b>	<b>4</b>
4611630	O	<b>Chroming Of Hose Tenna</b>	<b>0</b>
4611660	O	<b>Horizontal AE Mounting Bar Double Spring</b>	<b>5</b>
4614810	O	<b>AE Connections BOC/BOS, Hose Tenna</b>	<b>0</b>
<b>Tires &amp; Wheels</b>			
5060550	O	<b>FF: BR 20Ply 315/80R22.5 M863</b>	<b>32</b>
5104310	S	<b>RR: CN 14ply 295/75R22.5 Conti HDL3 LTL</b>	<b>0</b>
5190008	S	<b>Code-rear Tire Qty 08</b>	<b>0</b>
5215450	O	<b>FF: Accur 41012SP 22.5X9.00 Aluminum Wheel</b> Standard polish, 3.12 inch inset.	<b>-32</b>
5311510	O	<b>RR: Accuride 43644SP 22.5X8.25 Aluminum Wheel</b> Standard polish.	<b>-232</b>
5390008	O	<b>Code-rear Rim Qty 08</b>	<b>0</b>
5409300	O	<b>Wheel Guards, Tandem Axle</b> Between brake drum and wheel. Wheel guards provide a protective barrier to maintain the integrity between the brake drums and wheels to ensure the maximum life for your polished wheels.	<b>0</b>
5409310	O	<b>Wheel Guards, Steer Axle</b> Between brake drum and wheel. Wheel guards provide a protective barrier to maintain the integrity between the brake drums and wheels to ensure the maximum life for your polished wheels.	<b>0</b>
5409320	O	<b>Wheel Guards, Tandem Axle Between Wheels</b> Between wheels. Wheel guards provide a protective barrier to maintain the integrity between the brake drums and wheels to ensure the maximum life for your polished wheels.	<b>0</b>
<b>Fuel Tanks</b>			
5850110	O	<b>26" Alum 60 Gal Hydraulic Tank LH BOC Additional</b>	<b>0</b>
<b>Battery Box &amp; Bumper</b>			
6020050	S	<b>Steel LV Battery Box With Disconnect</b> RH BOC, Aluminum Cover, 12V Batt.	<b>0</b>
6111010	S	<b>Aluminum Bumper Swept Back Polished Without FEPTO</b> SBFA, two tow pins and step plates on top of bumper	<b>0</b>
6132450	O	<b>Heavy Duty External Tow Eye</b> IPO Standard, N/A With FETPO	<b>42</b>
<b>Cab &amp; Equipment</b>			





<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
6515690	S	<b>Vocational 115" BBC Alum Cab and Metton Hood SBFA</b> Stainless crown and grille with tilt assist.	0
6540160	S	<b>Thermal Insulation Package in Cab</b> The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	0
6540660	O	<b>SmartSound Cab Insulation Package</b> Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	65
6540740	S	<b>Peterbilt Keyless Entry</b> The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the drivers door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.	0
6700000	S	<b>No Sleeper Selected</b>	0
6800510	O	<b>Fender Lips 2.25" Wide</b>	6
6911100	S	<b>Peterbilt ST Driver</b> Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standand vinyl finish - color coordinate with interior color.	0
6921740	S	<b>Peterbilt ST Non-Adjustable Passenger Seat</b> Standard vinyl, no suspension cover, no seat back recline.	0
6930580	O	<b>Drivers Armrests - LH &amp; RH</b>	4
6930590	O	<b>Passenger Armrest - LH only</b> Required with Evolution LX seats, optional with Evolution ST Seats.	2
6931120	O	<b>Seat Belt Color Orange IPO Standard Black</b>	0
6939110	O	<b>Toolbox Under Passenger Seat</b> Non-Suspension Seat	0
6939400	S	<b>Air Ride Driver</b>	0
6939420	S	<b>High Back Driver</b>	0
6939470	S	<b>Vinyl Driver</b>	0
6939510	S	<b>Non-Air Ride Passenger</b>	0
6939520	S	<b>High Back Passenger</b>	0
6939570	S	<b>Vinyl Passenger</b>	0

Price Level: January 1, 2026

Deal: 567 EV rev 4

Printed On: 1/21/2026 6:11:52 PM

100% Complete

Date: January 22, 2026

Quote Number: QUO-1181916-V8T5Y3





Sales Code	Std/ Opt	Description	Weight
7000025	S	<b>Steering Wheel With Multi-Function</b> Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0
7000045	O	<b>High-Visibility Interior Grabhandles, Painted</b> Bright yellow interior grabhandle for vocational vehicles.	0
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0
7033810	S	<b>Platinum Interior - Ionic Gray</b>	0
7040150	O	<b>Rubber Floor IPO Carpet (Black Only)</b> Rubber Floor Covering in Cab. Standard in Prestige interior, optional in Platinum/Premier interiors.	-6
7110680	O	<b>Exterior Cab Entry Grabhandle</b> Textured; NFPA compliant. Available on Day Cab specifications only.	6
7210420	O	<b>Dark Window Tint IPO Standard Tint - Day Cab</b>	0
7210510	O	<b>3-Piece Glass Rear Cab Window, All Pieces Fixed</b>	12
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0
7230060	S	<b>1-Piece Curved Windshield</b>	0
7230360	S	<b>Power Door Locks and Power Window Lifts</b> Standard	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
7410040	O	<b>Outside Sunvisor - Stainless Steel</b> Not available with 2.1M high roof sleeper.	8
7510060	O	<b>Aero Rear View Mirror Housing, Bright Finish</b>	3
7514010	O	<b>Peterbilt Aero Rear View Mirror, Motorized</b> Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	3
7514050	S	<b>Look Down Mirror Over Passenger Door</b> with Black Housing	0
7610510	S	<b>Air Horn Mounted Underhood</b>	0
7722120	S	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>	0
7725740	O	<b>Midlevel Speaker Package For Cab</b> (4) Speakers	2
7728030	O	<b>Radio Mute When In Reverse</b> For automatic or automated transmission	0
7728040	O	<b>Bluetooth Phone and Audio Requires USB Port</b>	0

Price Level: January 1, 2026

100% Complete

Date: January 22, 2026

Deal: 567 EV rev 4

Quote Number: QUO-1181916-V8T5Y3

Printed On: 1/21/2026 6:11:52 PM



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>Weight</b>
7728050	O	<b>USB Port</b>	0
7782230	O	<b>Radio Antenna Mounted Logger Style</b> Models 579 and 567 Antenna Mounted LH Roof In Place Of Center Roof position.	2
7788335	S	<b>Global Telematics Hardware</b>	0
7789650	O	<b>Provisions For J1939 Connection</b> F/O Drivertech System	0
7850015	O	<b>Rear Wall Deep Record/Map Pocket</b>	2
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0
7852020	S	<b>Cab Air Suspension</b>	0
7852050	O	<b>Auto Reset Circuit Protection</b> Daycab and Sleeper	0
7852080	S	<b>Pull Out Tray/Work Surface Over Glove Box</b>	0
7871470	S	<b>Aero Close-Out Under Cab</b> Between cab and chassis fairing. For daycab only.	0
7900090	O	<b>Triangle Reflector Kit, Ship Loose</b> Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	13
7900310	O	<b>Fire Extinguisher, Mounted Outboard Driver Seat</b> Hazmat approval UL listed/rated ABC	8
7900401	O	<b>Cruise Control Inactive With Wipers On</b>	0
7900560	O	<b>Exterior Audible Alarm, Park Brake Not Set</b> With door open; city horn.	0
7901140	O	<b>Backup Alarm (87-112 DB)</b> Variable adjusting	6
8011410	O	<b>Drive Axle #1 Front Oil Temperature Gauge</b> 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	0
8011420	O	<b>Drive Axle #2 Rear Oil Temperature Gauge</b> 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	0
8021810	S	<b>Brake Application Air Pressure (Tractor)</b> Located in Digital Cluster Display.	0
8021820	O	<b>Brake Application Air Pressure (Trailer)</b> Located in Digital Cluster Display	0
8021880	O	<b>Trailer Reservoir Air Pressure</b> Located in Digital Cluster Display	0
8031120	O	<b>Warning Light Battery Disconnect, Switch Engaged</b> Marker light external mounted	0

Price Level: January 1, 2026

100% Complete

Date: January 22, 2026

Deal: 567 EV rev 4

Quote Number: QUO-1181916-V8T5Y3

Printed On: 1/21/2026 6:11:52 PM



Sales Code	Std/Opt	Description	Weight
8070100	O	<b>(4) Additional Dash Switches With Wiring</b> Located on dash panel C. Availability subject to dash space. Includes 4" 14 gauge wire with butt splice at rear of each additional switch.	1
8070260	O	<b>Switch To Deactivate ATC Traction Control</b> Bendix ATC is required on the specification. Switch is to temporarily disable the Traction Control in extreme conditions such as snow, ice or mud. The ATC warning light will display in a constant state.	0
8070610	O	<b>Dash Mtd E-PTO Speed Accel/Decel Switch</b>	0
8070855	S	<b>Main Instrumentation Panel (BEV)</b> Digital Cluster 15" Display includes: Speedometer, Power/Regen Gauge, Primary Air Pressure, Secondary Air Pressure, Usable State of Charge, Miles 'till Empty, eMotor Temp, Regen Braking Setting and Status	0
8110070	S	<b>Headlights Projector Module Pod</b> Fender mounted turn signals, projector module low beam, complex reflector high beam, pod mounted	0
8120990	S	<b>(5) Marker Lights, Aero LED</b> On roof, visor, or fairing	0
8133210	O	<b>Dash Switch Battery Power To J560</b> With Key On; W/Light,Buzzer Indicators	4
8133450	O	<b>(2) Brackets F/O Beacon/Strobe, Roof Mounted</b> (2) brackets for furnished by owner beacon / strobe lights roof mounted. Located above each door toward rear, includes switch and wiring.	4
8133960	S	<b>Daytime Running Lights</b> The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0
8134160	O	<b>Self-Canceling Turn Signal</b>	2
8140060	O	<b>LED Oval Stop/Turn/Tail/Backup</b> In tractor taper end of frame crossmember	-7
8152130	O	<b>(2) Load Lights, Bracket Mounted High Inboard</b> Back of cab / back of sleeper	7
<b>Paint</b>			
8500710	O	<b>Standard Paint Color Selection</b>	0
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0
<b>Shipping Destination</b>			
<b>Options Not Subject To Discount</b>			
9400088	O	<b>Base Warr: Batt Elec Pwrtrn Class 8</b>	0

Price Level: January 1, 2026

100% Complete

Date: January 22, 2026

Deal: 567 EV rev 4

Quote Number: QUO-1181916-V8T5Y3

Printed On: 1/21/2026 6:11:52 PM



Sales Code	Std/ Opt	Description	Weight
		12 Months/100K Mi (160Km)	
9400090	O	<b>Peterbilt Class 8 Standard Coverage</b> 1 year/100,000 Miles (160,000 km)	0
9408645	O	<b>SmartLINQ - 5YR Sub</b> PACCAR EV Powertrain	0
9408982	O	<b>Vehicle Layout</b> Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this.	0
<b>Miscellaneous</b>			
9409063	O	<b>State Of Registry: Illinois</b>	0
9409712	O	<b>BEV/ DAY CAB / PLATINUM INTERIOR (EDP) 3</b>	0
9409843	O	<b>Peterbilt Sourcewell Program Code</b> Applicable with Marketing Programs Only. No CAR allowed	0
9499985	O	<b>Unit Not Drivable w/o Modifications</b> There is an option on the order that makes the option is not legally allowed to be driven without modification. This does not prevent Active from making modifications (temporary marker lights) to have it is the lead truck.	0

## Promotions

## Special Requirements

Special Requirement 1 0098170

Special Requirement 2

Special Requirement 3

Special Requirement 4

## Order Comments

Price Level: January 1, 2026

Deal: 567 EV rev 4

Printed On: 1/21/2026 6:11:52 PM

100% Complete

Date: January 22, 2026

Quote Number: QUO-1181916-V8T5Y3



Total Weight (lbs)

22,394

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### PRICING DISCLAIMER

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



Price Level: January 1, 2026

Deal: 567 EV rev 4

Printed On: 1/21/2026 6:11:52 PM

100% Complete

Date: January 22, 2026

Quote Number: QUO-1181916-V8T5Y3



**Shipping Destinations**

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------