



## Shop Order

Village of Oak Park FD  
260 Madison St.  
Oak Park, IL 60302

ARV  
Kevin Hunter

Exp. Date: 09/01/2020  
Quote No: 10062-0055  
TYPE I: 172T1LWXFT 172 LWB Ford T1 X Series Top Level  
GENERAL: GEN\_INFO X \*\*\*\*\*BID STANDARDS\*\*\*\*\*  
CHASSIS: F-4/550LB \*\*\*\*\*F-Series 108ca CHASSIS\*\*\*\*\*  
CONVERSION: 172T1LWBFX 172 x 96 T-1 LWB Ford X-Series, Conversion  
BASE: 172T1LWBX 172 x 96 T-1 LWB Ford X Base Price

09/01/2020

Job/Order No: Proposal

Page 1

PART NO	S	DESCRIPTION	QTY
= *****BID STANDARDS***** - 15.015 03/09/20 =			1
00-00-0107		-- Order Date: Post July 1, 2019	1
00-00-0113	<	-- Ambulance Built to Star Of Life KKK-A-1882-F Certification, Latest Revision	1
Exceptions to be noted on final sticker.			
00-10-0015		Vehicle Quantity (Vehicles)	1
00-91-0002		BODY NUMBER:	1
00-91-0005		-- MICKEY BODY DUE DATE :	1
00-91-0003		CHASSIS VIN NUMBER:	1
00-91-0024		ACCOUNT MANAGER: Mikael Blevins	1
00-91-0027	S	REFERENCE UNIT #: 18OF 23541XA	1
00-91-0028	S	RE-WRITE DATE : 3-16-20	1
00-91-0040		SEAT BELT POSITIONS MODS	1
00-91-0042		-- CAB SEAT BELT MOD:	1
00-91-0044		-- Total: 2 Positions	1
00-91-0050		-- REAR SEAT BELT MOD:	1
00-91-0054		-- Total: 4 Positions	1
00-99-9000		Revision Level: 0 - Zero - ORIGINAL VERSION	1
00-99-9030		Change Order Level: 0 - Zero - ORIGINAL VERSION	1
Aluminum Composite Cabinet Configuration			1
= *****F-Series 108ca CHASSIS***** - 15.015 03/09/20 =			1
01-1F-0000		Type I Modular Ambulance	1
01-AP-2F49	<	2020 Ford F-550 4x4 DRW REG CAB, 193" WB XLT V8 Gasoline	1
Special order chassis, lead time of 14-16 weeks may apply			
Take note of chassis default items, especially single battery.			
01-1F-0091	<	-- Engine: 7.3L Gasoline V-8 - F-series Ambulance approved	1
Engine hour meter display through message center			
01-1F-0092		-- Chassis Front engine hood Insulation Not included by OEM Ford on all XLT	1

PART NO	S	DESCRIPTION	QTY
01-1F-0100		/-- OEM Installed Engine Block Heater: Included on Chassis Not connected	1
01-1F-02CM		/-- Cab Interior Color: Medium Earth Gray F-series 2017	1
01-1F-02T5		/-- F-Series 193" wheelbase reg cab LWB	1
01-1F-03PU		/-- GVWR: 18,000 pounds, FAWR: 7,000, RAWR: 13,660 (4x2)	1
01-1F-047A	<	/-- 47A - Ambulance Prep Package - F-Series (requires chassis to be ordered, REV Stock chassis are ordered 47L)	1
01-OE-47A4		/-- Throttle: Ford High Idle	1
01-1F-0502		/-- Alternator: Dual Extra heavy duty Alternator OEM Total 397Amp	1
01-1F-0505		/-- Battery; OEM Single 750 CCA, 78 Amp Hours	1
01-FL-TI06		/-- Tire, SPARE: Matching, Random Make	1
01-FM-TI01		/-- Location: Shipped Loose	1
01-TU-0112		/-- Jack and Tire Tools: Install behind Passenger's seat	1
01-FM-4WH2	<	/-- Aluminum Wheels (F-450/550): Ford Option 64D 19.5" Special order chassis Requires Special Order Chassis	1
01-FM-4WH9	<	/-- Wheel Finish: Polished SS Lug Nut Covers & Centers (DISCONTINUED) BOM not setup	1
01-FM-DL01		/-- Cab Door Locks: Power	1
01-FM-DTRL		/-- Daytime Running Lights: Ford OEM	1
01-FM-DTRQ		/-- Ford F series High center mount brake light ordered with chassis	1
01-FM-TIR3		/-- Tires: F-4/550, All season, Random Mk 225/70 R19.5, LR F	1
01-RR-05B6		/-- Radio, F-series: OEM AM/FM/Satellite w/ 5 cab speakers 8" Display 2020 +	1
01-SY-0005	<	/-- Ford SYNC 3 Voice Activated, in vehicle connectivity 913 2020 XLT std- all Includes 8" LCD Capacitive touchscreen in centerstack with swipe capability. 911 assist, 2 smart charging USB-C ports. Includes Sirius XM Satellite Radio with 6 mont prepapd subscription (continental USA only).	1
03-EA-47PR		/-- Side Mirrors, OEM (F-Series), Pwr Glass, Heated, manual Telescopic	1
04-SU-1101		/-- Ford OEM Front Suspension Coil Spring Std F-450/550	1
04-SU-1729	<	/-- Rear Suspension: F-550 Liquid Spring, 2017+ *NOTE: If Oxygen Lift is installed, then if the O2 Cmpt Door is open, the kneeling suspension will not dump until door is closed* Part; SUSP-DS147FS3 Rated for 13,660 GAWR	1
01-TT-0208	<	/-- ""DETAIL"" Liquid Rear Suspension Decal Install Prior to delivery, detail department is to install a Black Decal on the dash:	1
04-SU-0602	S <	/-- Kneeling Feature: Enable Switch Located in face RR Cabinet and in Cab Console Switch location shall be within reach of an attendant standing on the ground, outside the module. It shall be recessed from the wall surface.	2
04-SU-0612	S	/-- LOCATION: Sw panel on Face of CS cabinets near RA door and in Cab Console	2
04-SU-0610		/-- Kneeling Feature: Activated by TRAILING rear access door	1
04-SU-0651		/-- Exhaust system termination point: OEM Location, Rt Rear	1
04-SU-2022	<	/-- Liquid spring controller shipped loose with completed unit Dealer to install with customer on arrival	1
04-SU-03F6		/-- Rear Stabilize (Anti-Sway) Bar: OEM, Ford F-450/550	1
ZZ-ZZ-ZZZZ		== 172 x 96 T-1 LWB Ford X-Series, Conversion - 15.015 03/09/20 ==	1
06-EA-01FC	<	Tire valve extensions Type 1 F series with Alcoa Aluminum Wheels Install (1) EXTE-VALV04 (1) EXTE-VALVPLUG in outer rim to support valve extension	1
BODY Generation 9			1
01-X0-0001	<	/-- Body Certification Provided to Specification The Body Manufacturing group certifies that this Ambulance Modular body has been constructed of materials and methods that meet or exceed the standards as required by	1

PART NO	S	DESCRIPTION	QTY
		the AEV Generation 9 Body Specification of December 11th, 2018 as published. The body shall be built and constructed to the submitted work order and the AEV Generation 9 build standards without exception. Any Deviations to the work order or Generation 9 build standards must have written authorization prior to body delivery to AEV by the AEV Body Engineer on file.	
02-00-0002	<	-- Body Build Information Body Number; Account Manager; Chassis Type : Mickey Body Due Date;	1
02-00-0003	<	-- ALL DIMENSIONS ON ORDER WILL HAVE A VARIABLE OF + OR - 1/4" Unless specified as a minimum dimension.	1
<b>02-B2-XO92</b>	<b>S</b>	<b>Body, Mod: Type 1 LWB, 172" x 96" x 74" Interior HR - 6" Body Drop x</b>	<b>1</b>
<b>02-00-0006</b>	<b>S</b>	<b> -- Headroom: 76/74" Finished Interior - Ducted A/C</b>	<b>1</b>
02-00-0060		-- Compartment and Entry door Full length Stainless Steel Hinges std	1
02-B0-CC01	<	-- Compartment Construction: STANDARD, Unless Specified Otherwise Sides and Back: .100 Polished Aluminum Diamond Plate Compartment Ceiling: .090 Aluminum Sheet	1
02-B0-SFL0	<	-- Compt Floors: Sweep-out, even with bottom door jamb Unless Specified Otherwise.	1
02-B0-CC41		-- Compartment floor thickness .125" standard	1
02-B0-CC18		-- Compartment Ventilation - Flap style #VT-2495-A01, STD	1
02-B0-CEX2		-- Curbside Entry Door (CSE): 84.813"H x 31.0"W X w/6" drop	1
<b>02-B0-0005</b>	<b>S &lt;</b>	<b> -- Door Strap &amp; Foot man loops Kit per module body door</b> <b>(1) STRA-DOOR Door strap kit for Seat belt style door strap, installed with Footman loops. This strap is to protect against overload of door gas strut assembly.</b> <b>(1) foot man loop in each end of the strap mounted to the door and the module.</b>	<b>1</b>
		<b>NOTE: MOUNTED ON C/S DOOR DOWN LOW</b>	
02-B0-09B2		-- C/S Door Check : Double Action Gas Shock	1
04-EA-09B1		-- Door Swing Angle: Set to 90-100 degrees	1
<b>02-B0-CESL</b>	<b>S &lt;</b>	<b> -- Curbside Entry Door (CSE) Location: Standard, Rearward of M-7 Compt if</b> <b>Optioned</b> <b>M5, M7, and CSE Door Handles to be Aligned</b> <b>M1 AND M3 Compartment Door Handles to be Aligned</b>	<b>1</b>
ZZ-ZZ-ZZZZ		--	1
02-B1-SWX2	<	-- Step Well, CURBSIDE Entry Door, 2-Step Embossed Diamond Plate (2) Steps : 9" Risers x 10" Tread	1
05-IL-09X1	<	-- Light, Step Well: 3" Kinequip #4302S, Chrome, LED, STD Light shall come on with CS door only.	1
02-BC-0604		-- Talk through, Cab to Mod Window (T1) With Sliding Window 2017+ F	1
02-BC-0700	<	-- Cab Roof Support : 3/16" x 3" Steel Plate, Per Engineering Drawing Between cab headliner and bottom side of cab roof to prevent oil canning.	1
<b>02-BD-0120</b>		<b> -- Body Drop: 6" Both Sides, Ahead of Rear Wheels</b>	<b>1</b>
<b>02-X1-M149</b>	<b>S &lt;</b>	<b> -- M-1 Compt (LF): 69.5" H x 22.125" W x 20.0" D</b> <b>M1 and M3 Door Handles to be Aligned</b>	<b>1</b>
<b>02-B0-CCM1</b>	<b>&lt;</b>	<b> -- M-1 Compartment Construction: Smooth Aluminum ILOS</b> Sides and Back: .090 Aluminum Sheet Compartment Ceiling: .090 Aluminum Sheet	<b>1</b>
<b>02-B0-CC09</b>		<b> -- Compartment Door Panel: Smooth Aluminum</b>	<b>1</b>
<b>02-B0-CFM1</b>		<b> -- Compartment Surface Finish: Speed Liner, Black - M-1</b>	<b>1</b>
<b>02-B0-CFN1</b>	<b>S &lt;</b>	<b> -- Component Finish (Shelf/Tray/Divider): Speedliner Black Each</b> <b>NOTE: Speedline Divider Black</b>	<b>1</b>

PART NO	S	DESCRIPTION	QTY
02-B0-CC16		-- Compartment Door Ventilation - small punched half moon Louvered Door	1
02-B0-SWFL		-- Compt Floor: Sweep-out, even with bottom door jamb.	1
02-B0-CC41		-- Compartment floor thickness .125" standard	1
02-BC-10A5		-- Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch	1
02-B0-09B0		-- Compt Door Check: Double Action Gas Shock	1
04-EA-09B1		-- Door Swing Angle: Set to 90-100 degrees	1
<b>04-TS-0037</b>		<b>-- Storage in Oxygen compartment Requested Exception to KKK-F Specifications</b>	<b>1</b>
<b>04-TS-1400</b>	<b>S &lt;</b>	<b>-- Divider, Vertical, Full compartment height, alum, Fixed</b> <b>NOTE: Divider Located 11" from wall #1</b>	<b>1</b>
<b>11-YZ-0903</b>		<b>-- Non-Compliant to 3.11.3 KKK-F Storage in Oxygen Compartments Notice</b>	<b>1</b>
<b>11-ZZ-0904</b>	<b>&lt;</b>	<b>-- CAAS Exception C.11.3.9 Storage in an Oxygen Compartment</b> an exception to CAAS GVS 1.0 is taken for the following condition. Subpart 9. The oxygen storage area shall be configured and used only for the main oxygen cylinder and associated plumbing.	<b>1</b>
<b>05-EL-49X6</b>	<b>&lt;</b>	<b>-- Light, Cmpt: Vista LED Rope Style #FSW1F, ILOS X-Series units</b> MTB Note: No light hole required	<b>1</b>
08-B1-02LI		-- Prep for 02 Lift: NONE	1
09-ZZ-ZZZZ		--	1
02-X1-M1AD		-- M-1A Comp (LF Upper): 72 HR, 17.56" H x 22.125" W x 20.0" D	1
02-B0-CC02	<b>&lt;</b>	-- Compartment Construction: STANDARD Diamond Plate Sides and Back: .100 Polished Aluminum Diamond Plate Compartment Ceiling: .090 Aluminum Sheet	1
02-B0-CC08		-- Compartment Door Panel: Diamond Plate	1
12-DC-GA10		-- Compartment Finish: Diamond Plate Standard	1
02-B0-CC16		-- Compartment Door Ventilation - small punched half moon Louvered Door	1
02-B0-SWFL		-- Compt Floor: Sweep-out, even with bottom door jamb.	1
02-B0-CC41		-- Compartment floor thickness .125" standard	1
02-BC-10A0		-- Compartment Door: SINGLE DOOR, 1-point Latch	1
02-B0-09B0		-- Compt Door Check: Double Action Gas Shock	1
04-EA-09B1		-- Door Swing Angle: Set to 90-100 degrees	1
05-EL-40XB	<b>&lt;</b>	-- Light, Compt, LED, M-1A (LF Upper): Intertek Model No ZY-156-LEDC, STD MTB Note: 1" Hole, Centered in Compartment ceiling	1
12-ZZ-ZZZZ		--	1
<b>02-X1-M276</b>	<b>S &lt;</b>	<b>-- M-2 Compt (LFM): 36" H x 49.875" W x 20.0" D</b> <b>Custom Box Off for Interior Cabinet-CUSTOM</b>  <b>Note to Mickey: See Custom Drawings</b>	<b>1</b>
<b>02-B0-CC02</b>	<b>&lt;</b>	<b>-- Compartment Construction: STANDARD Diamond Plate</b> Sides and Back: .100 Polished Aluminum Diamond Plate Compartment Ceiling: .090 Aluminum Sheet	<b>1</b>
<b>02-B0-CC08</b>		<b>-- Compartment Door Panel: Diamond Plate</b>	<b>1</b>
<b>12-DC-GA10</b>		<b>-- Compartment Finish: Diamond Plate Standard</b>	<b>1</b>
<b>02-B0-SWFL</b>		<b>-- Compt Floor: Sweep-out, even with bottom door jamb.</b>	<b>1</b>
<b>02-B0-CC41</b>		<b>-- Compartment floor thickness .125" standard</b>	<b>1</b>
<b>02-B1-BION</b>		<b>-- Bio-Waste None;</b>	<b>1</b>
<b>ZZ-ZZ-ZZZZ</b>		<b>--</b>	<b>1</b>
<b>02-B1-ELEH</b>		<b>-- Electrical Compartment : Circuit Board Storage relocated to cabinet H</b>	<b>1</b>
<b>02-BC-10D0</b>		<b>-- Doors, Compartment, DOUBLE DOORS (std)</b>	<b>1</b>
<b>02-B0-09B0</b>		<b>-- Compt Door Check: Double Action Gas Shock</b>	<b>1</b>
<b>04-EA-09B1</b>		<b>-- Door Swing Angle: Set to 90-100 degrees</b>	<b>1</b>
<b>04-TS-11D3</b>		<b>-- M-2 Shelf, Adjustable, Ext: .125 Alum, 2" Upward lip</b>	<b>1</b>
<b>04-TS-4010</b>		<b>-- Shelf Bracket: CPI 90 Deg with Slotted Holes</b>	<b>1</b>

PART NO	S	DESCRIPTION	QTY
05-EL-49X6	<	/-- Light, Cmp: Vista LED Rope Style #FSW1F, ILOS X-Series units MTB Note: No light hole required	1
05-HA-13HY	<	/-- Condenser, 12V: ACC, Dual Fan, Front of Body over Cab COND-ACT1A cond-act1a	1
04-HA-1310	<	/-- ARCTIC WEDGE Condenser Cover: Install on Front Body over Condenser part #WEDGE-HVAC Use of the wedge is subject to engineering review and approval for Light duty Type III models. A reduction in light sizing above the wedge may be required.	1
12-B0-0002		/-- Painted Part- Painted White YZ Std	1
06-RR-13Z0		/-- Standard Conduit: 1-1/2", with pull wire	1
06-RR-13O4	S	/-- CONDUIT ORIENTATION POINT: M-1A compartment	1
06-RR-13T3		/-- CONDUIT TERMINATION POINT: Behind A/A Board (Panel)	1
06-RR-13Z1		/-- Conduit #2 1-1/2" diameter, with pull wire, Type 1 units Std	1
06-RR-13O1		/-- CONDUIT ORIENTATION POINT: Electrical Circuit board cabinet	1
06-RR-13T2		/-- CONDUIT TERMINATION POINT: Behind Driver's seat	1
09-ZZ-ZZZZ		/--	1
02-X1-M379	S <	/-- M-3 Compt (LR): 61.5" H x 35" W x 10/20.0" D M1 and M3 Door Handles to be Aligned  Note: Half Depth Compt in Upper Section CUSTOM BUILD  Note to Mickey: See Custom Drawings	1
02-B0-CC02	<	/-- Compartment Construction: STANDARD Diamond Plate Sides and Back: .100 Polished Aluminum Diamond Plate Compartment Ceiling: .090 Aluminum Sheet	1
02-B0-CC08		/-- Compartment Door Panel: Diamond Plate	1
12-DC-GA10		/-- Compartment Finish: Diamond Plate Standard	1
02-B0-SWFL		/-- Compt Floor: Sweep-out, even with bottom door jamb.	1
02-B0-CC41		/-- Compartment floor thickness .125" standard	1
02-BC-1000		/-- Compartment Doors: DOUBLE DOORS, ILOS single	1
02-B0-09B0		/-- Compt Door Check: Double Action Gas Shock	1
04-EA-09B1		/-- Door Swing Angle: Set to 90-100 degrees	1
04-TS-1016	XS <	/-- (4) Tool plates on uni-strut, .125 Smooth Aluminum/DA sanded in compartment All (4) plates to be DA sanded Aluminum ONE PLATE ON WALL #2 UPPER SECTION, ONE PLATE ON WALL #2 LOWER SECTION, ONE PLATE ON WALL #1 LOWER SECTION AND ONE PLATE ON WALL #3 LOWER SECTION.  AEV TO INSTALL 2 CUSTOMER SUPPLIED SCBA BRACKETS IN THE M-3 COMPT ON WALL #2 LOWER PLATE. DIRECTIONS FOR THE INSTALL ARE IN THE BOX WITH THE BRACKETS. PLEASE REFERENCE DIRECTIONS BEFORE INSTALLING.	4
04-TS-1016	X <	/-- AEV TO INSTALL (2) SCBA BRACKETS AEV TO INSTALL 2 CUSTOMER SUPPLIED SCBA BRACKETS IN THE M-3 COMPT ON WALL #2 LOWER PLATE. DIRECTIONS FOR THE INSTALL ARE IN THE BOX WITH THE BRACKETS. PLEASE REFERENCE DIRECTIONS BEFORE INSTALLING.	2
05-EL-49X6	<	/-- Light, Cmp: Vista LED Rope Style #FSW1F, ILOS X-Series units MTB Note: No light hole required	1
09-ZZ-ZZZZ		/--	1
02-X1-M574	S <	/-- M-5 Compt (RR): 74 HR, 84.812" H x 25.625" W x 21." D M5, M7, and CSE Door Handles to be Aligned	1
02-B0-CCM5	<	/-- M-5 Compartment Construction: Smooth Aluminum ILOS Sides and Back: .125 Aluminum Sheet Compartment Bottom: .125 Aluminum Sheet	1



PART NO	S	DESCRIPTION	QTY
		Compartment Ceiling: .090 Aluminum Sheet	
02-B0-CC09		/-- Compartment Door Panel: Smooth Aluminum	1
02-B0-CFM5		/-- Compartment Surface Finish: Speed Liner, Black - M-5	1
02-B0-CFN1	S <	/-- Component Finish (Shelf/Tray/Divider): Speedliner Black Each	3
		<b>NOTE: Divider and Shelves Speedlined Black</b>	
02-B0-CC12	<	/-- Compartment Ventilation - Compartment Ceiling O O O O MTB NOTE: hat channel with three (4") holes above the hat at the ceiling level.	1
02-B0-CC16		/-- Compartment Door Ventilation - small punched half moon Louvered Door	1
02-B0-SWFL		/-- Compt Floor: Sweep-out, even with bottom door jamb.	1
02-B0-CC41		/-- Compartment floor thickness .125" standard	1
02-BC-10A5		/-- Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch	1
02-B0-09B0		/-- Compt Door Check: Double Action Gas Shock	1
04-EA-09B1		/-- Door Swing Angle: Set to 90-100 degrees	1
04-TS-1200	S <	/-- M-5 Shelves, (2) Adjustable, Ext: .125 Aluminum, Partial Width 2" lips upward	2
		<b>NOTE: Shelves to be From Divider to Wall #3 With Bottom Shelf 42" up from Floor</b>	
04-TS-4010		/-- Shelf Bracket: CPI 90 Deg with Slotted Holes	2
04-TS-19M5	S	/-- M-5 Divider, Fixed, (1) 14x60 H	1
04-TS-1003		/-- Divider Material: .188 Aluminum Sheet	1
04-TS-STR1	S <	/-- Strap: 2" Webb Seatbelt buckle chrome footman loops This strap is to secure things from moving while the vehicle is in motion.	1
		<b>NOTE: Strap From Wall #1 to Divider</b>	
04-TS-STR2		/-- 2" Footman Loops: Locate back from jamb	1
04-TS-20RB	S <	/-- Retainer Bar: Installed In Exterior Compartment Each <b>NOTE: Mount 6" Retainer Bar across top of M5 Compt 69" up from Floor to hold back boards in place</b>	1
04-TS-STR3	S <	/-- Strap: 2" Webb, w/ Chrome Metal Seatbelt buckle w footman loops IATS This strap is to secure things from moving while the vehicle is in motion, and is not designed to be a crash stable securing device.	1
		<b>NOTE: Strap From Divider to Wall #3 Below Shelf</b>	
04-TS-STR2		/-- 2" Footman Loops: Locate back from jamb	1
05-EL-40X5	<	/-- Light, Compt, LED, M-5 (RR): Intertek Model No ZY-156-LEDC, STD MTB Note: 1" Hole, Centered in Compartment ceiling	1
09-ZZ-ZZZZ		/--	1
02-M1-X600		/-- M-6 Compt (RRFwd): Delete	1
02-X1-M775	S <	/-- M-7 Compt (RF): 72 HR, 46.75" H x 25.25" W x I/O to ALS M5, M7, and CSE Door Handles to be Aligned	1
02-BC-10A5		/-- Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch	1
02-B0-09B0		/-- Compt Door Check: Double Action Gas Shock	1
04-EA-09B1		/-- Door Swing Angle: Set to 90-100 degrees	1
05-EL-49X6	<	/-- Light, Cmpt: Vista LED Rope Style #FSW1F, ILOS X-Series units MTB Note: No light hole required	1
12-ZZ-ZZZZ		/--	1
02-X1-M847	S	/-- M-8 Compt (RF): Batt Drawer 16" H x 25.25" W x 20" D	1
02-B0-CC02	<	/-- Compartment Construction: STANDARD Diamond Plate Sides and Back: .100 Polished Aluminum Diamond Plate Compartment Ceiling: .090 Aluminum Sheet	1
02-B0-CC08		/-- Compartment Door Panel: Diamond Plate	1
12-DC-GA10		/-- Compartment Finish: Diamond Plate Standard	1

PART NO	S	DESCRIPTION	QTY
02-BC-10E0		<i>/-- Drawer Front: 2-point latch</i>	1
05-EL-40M8		<i>/-- Light, Compt, M-8 (Batt): NONE</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
02-X1-RA02		<i>/-- Rear Access Doors: 46.75" Wide x 60.625" High</i>	1
09-IN-3STX	<	<i>/-- Insulation: All Module Doors, 2" Black Foam, X-Series units</i> #INSU-ARM2	1
09-IN-3STY	<	<i>/-- Insulation: All Module Doors, Black Sound Proofing, X-Series units</i> #INSU-KSU	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
		<b>WELDING - CELL 1</b>	1
04-AS-1800		<i>/-- Stainless Steel - Sill protection: For the following compartments</i>	1
04-AS-18M0	<	<i>/-- M-1A: Left Front Compartment - Single Bend</i> REV to fabricate	1
04-AS-18M1		<i>/-- M-1: Left Front Compartment - Single Bend</i>	1
04-AS-18M2		<i>/-- M-2: Left Front Middle Compartment - Single Bend</i>	1
04-AS-18M3		<i>/-- M-3: Left Rear Compartment - Single Bend</i>	1
04-AS-18M5		<i>/-- M-5: Right Rear Compartment - Single Bend</i>	1
04-AS-18M7		<i>/-- M-7: Right Front Compartment - Single Bend</i>	1
04-AS-06A0		Fuel Fill: CPI C1045, Open Housing, Polished Bezel - (Std)	1
04-AS-0204	S <	<i>/-- Fuel over Fill protection plate: Stainless Steel</i> Custom Stainless steel shield With Lip Under Fuel Fill (Reference 19OF 24770XA Greater Round Lake)	1
04-AS-080N		<b>Urea fill DELETED GASOLINE ENGINE CHASSIS NO HOLE CUT</b>	1
04-AS-0370		<i>/-- Wire/Hose Cover : Diamond Plate, Between Cab &amp; Module</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
04-AS-0382	<	<i>/-- Pass-Thru cab mounted wind deflector - Aluminum Diamond Plate</i> AEV Weld shop builds and installs, Attaches to Cab side of bellows mount. Same width as bellows mount with short down turned sides. Secured on sides to bracket. Small up-turned lip at back of wind deflector. non-Painted	1
04-BW-ABY1	<	<i>/-- Bumper, Rear: X-Series 96" Wide w/ Embossed D/P Pontoon Covers</i> X-Series Design. Purchasing NOTE : Special Order Delete standard rear bumper assembly from Mickey Body	1
04-BW-FLIW	<	<i>/-- Step, Center:2" x 9" Bar Grate, flip-up, recessed</i> Standard with X series,> AEV builds MTB delete flip up step.	1
04-EA-1306		<i>/-- Dock Bumpers: Rubber D-Shape, 4" H x 18" W x 4" Thick X -series</i>	1
04-BW-RF20	<	<i>/-- Fenders, Rear: Rubber Extruded, Black</i> MTB #7215439	1
04-BW-DN00		<i>/-- Corner Caps "X Series:</i>	1
04-BW-DN23	<	<i>/-- Front Corner Caps: 24.0" High, Alum Diamond Plate</i> NOTE: Standard Front Corner Caps from Mickey Body	1
04-BW-DN33	<	<i>/-- Rear Corner Caps: 24" High, Polished Diamond Plate, X-Series</i> Purchasing NOTE: Special Order from vendor. Delete standard rear corner caps from MTB	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
04-BW-DP2K	<	<i>/-- Rear Kick Plate: Smooth Aluminum X recessed flip area, No recessed tag</i> ILOS X Purchasing NOTE : Special Order from CCP. Delete standard rear kick-plate from Mickey Body	1

PART NO	S	DESCRIPTION	QTY
		CCP note, Welds to be on backside at joints. New print available to show this kickplate. PLAT-23541XA	
<b>04-AS-0500</b>	<	<b>/-- Holder, License Plate, CPI C30002, Recessed choice of lights</b> Delete standard Tag cut out. HOLD-12C	<b>1</b>
<b>04-AS-0522</b>	<b>XS</b>	<b>/-- Location, Driver Side Rear Under Turn Signal</b>	<b>1</b>
<b>05-EL-44TN</b>		<b>/-- Tag Light: Kinequip LED #132703C</b>	<b>1</b>
<b>05-EL-44XL</b>	<	<b>/-- Rear Flip up Step Lights, (2), Kinequip LED Strip light #KFL-SLC8</b> Mounted above rear bumper flip up step, in kick-plate recess	<b>1</b>
<b>ZZ-ZZ-ZZZZ</b>		<b>/--</b>	<b>1</b>
04-BW-DP93	<	-- Front Stone Guards: 24.0" High, Alum Diamond Plate If there is a body drop, add the appropriate height to Stone Guards.	1
04-BW-DPY9	<	-- Skirt Rails: Polished D/P, w/ 12-inch LED Lights, X-series >> MTB, >Built by AEV	1
05-EL-SKXB	<	-- Skirt rail Lights, Front Pair 12" LED (1) Each side, forward position, in front skirt rail	1
<b>05-EL-SKV2</b>	<	<b>/-- (2) Skirt rail LED Strip Lights, Red/Red 12" X-series</b> NOTE: Mount Red On TOP and Clear on Bottom	<b>1</b>
05-EL-SKXC	<	-- Skirt rail Lights, Middle Pair 12" LED (1) Each side, rear position, in front skirt rail	1
<b>05-EL-SKV2</b>	<	<b>/-- (2) Skirt rail LED Strip Lights, Red/Red 12" X-series</b> NOTE: Mount Red On TOP and Clear on Bottom	<b>1</b>
05-EL-SKXD	<	-- Skirt rail Lights, Rear Pair 12"-LED (1) Each side, in rear skirt rail	1
<b>05-EL-SKV2</b>	<	<b>/-- (2) Skirt rail LED Strip Lights, Red/Red 12" X-series</b> NOTE: Mount Red On TOP and Clear on Bottom	<b>1</b>
05-EL-SKZ1		-- Skirt rail Lights Switched: Separate Switch in the Cab console	1
05-EL-SLHX	<	-- LED Ground Lights: (6) Kinequip White 12" -LED lights, In Skirt rails x Lights to stay on 30 seconds after all doors are closed.	1
05-EL-SLGY	<	-- LED Ground Lights Switched: The underbody lights work off a switch in the console or with any entry or compartment door. Lights stay on for 30 seconds after all doors are closed.	1
04-DE-0010		-- Rear Deflector: NONE	1
<b>04-EA-09A0</b>	<b>S</b>	<b>&lt; (2) Rear Door Hold Opens: Grabber Style, each door</b> NOTE: Locate at Bottoms of Doors	<b>1</b>
04-EA-14X5	<	Running Boards: Embossed D/P, Bar-Grate Insert, X Series - 2 Door X- STD F 2017 Bar grate insert 16" long BOAR-XF2017	1
<b>04-EA-1122</b>		<b>/-- Mud Flaps Front: Modular, Rubber with AEV/Rev Logo std</b>	<b>1</b>
04-EA-1132		-- Mud Flaps Rear: Modular, Rubber AEV LOGO	1
05-EL-39X4	<	-- Lights, Cab Step: 2" White LED , surface mount on box front, (#TOCACCCR) - x ser Chrome Flange Activate by Cab Doors. Constant Hot. (2) LITE-TOC (2) Lite-TFLANGEC	1



PART NO	S	DESCRIPTION	QTY
ZZ-ZZ-ZZZZ		--	1
		EXTERIOR LIGHTING / HEAT/AC / INSULATION - CELL 2	1
05-00-0002	S <	Aero Clave Exterior Plug ADP-PT in exterior compartment to interior nozzle part; KITS-ADPPT	1
		NOTE	
		parts included in kit	
		(1) Stainless steel hose mounting bracket 9" tall x 4.25 inch wide x 2.75 inch deep to mount to wall #3 in M3 compartment to wind the hose around	
		(2) 10 feet long 1/4" diameter red and blue polyurethane hose that run from port in M3 compartment wall up through box interior to upper patient interior corner to upper rear pad to nozzle location	
		(1) Stainless steel and plastic spray fog nozzle	
		(1) 8 foot plug and play ADP treatment hose that extends from M3 compartment to treatment machine owned by EMS service. Machine not included.	
05-EL-1800		CORNER CAP LED ICC/WARNING LIGHTS	1
05-EL-18F0		-- Front Corner Cap LED ICC/Warning Lights: Warnings RED/WHITE	1
05-EL-18FX	<	-- Front Center ICC Lts: (3) AMBER Kinequip LED #KML-A-SC	1
		Switch w/ Headlights.	
ZZ-ZZ-ZZZZ		--	1
05-EL-18R5		-- Rear Corner Cap LED ICC/Warning Lights: Warnings RED/AMBER	1
05-EL-18RX	<	-- Rear Center ICC Lts: (3) RED Kinequip LED #KML-R-SC	1
		Switch w/ Headlights	
ZZ-ZZ-ZZZZ		--	1
06-SW-CC01		-- ICC Warning Lights Switched: Primary Only	1
ZZ-ZZ-ZZZZ		--	1
05-EL-2503	S <	LED Lights, Patient on Board, X-Series Units	1
		Install lights in the following locations :	
		M-1A Compartment - On Door panel, Outer lower corner	
		M-1 Compartment - On Door panel, Outer Edge, Centered Top to Bottom	
		M-2 Compartment - On Forward Door panel, Upper outer corner	
		M-2 Compartment - On Trailing Door exterior, Upper outer corner	
		M-3 Compartment - On Door panel, Outer Edge, Centered Top to Bottom	
		M-3 Compartment - On Trailing Door exterior, Centered Top to Bottom	
		M-5 Compartment - On Door panel, Outer Edge, Centered Top to Bottom	
		M-6 Compartment - On Door panel, Outer lower corner	
		M-7 Compartment - On Door panel, Outer Edge, Centered Top to Bottom	
		C/S Entry Door - Below Center panel, Outer Edge	
		Rear Entry Doors - (1) each door, Below Center panel, Outer Edge	
		A Total of (12) Lights	
05-EL-252C		-- Red/White LED POB Light, Kinequip Each, X-Series Units	12
05-EL-256X		-- Lights Switched with Entry Door Switch	1
ZZ-ZZ-ZZZZ		--	1
05-EL-42XX		TAIL LIGHTS	1
05-EL-23X2		-- Tail Lights, Whelen LED Combinations , STD, X-Series	1
05-EL-19MO	<	-- Side Marker Lights: (2) RED Kinequip LED No 112401RD	1
		Switch w/ Headlights.	
05-EL-2418	S	-- Whelen M9 & M6 Series, Tail Lights	1
05-EL-2424	S <	-- Stop/Tail, Whelen M9 Series, LED, Pair	1
		Mounted in Kick Plate	
05-EL-2430	S <	-- Turn, Whelen M9 Series, LED, Pair	1
		Mounted above the License Plate Holder on the street side and directly across on the curbside	
05-EL-2432	S <	-- Back up, Whelen M6 Series, LED, Pair	1
		Mount next to brake lights on the kick plate	

PART NO	S	DESCRIPTION	QTY
05-PH-LF14		/-- M9 Series Flange, Chrome Plated, Std: Two Pair	1
05-PH-LF20		/-- M6 Series Flange, Chrome Plated, Std: Each	2
ZZ-ZZ-ZZZZ		/--	1
05-EL-4305		< Patient Area Turn/Stop Light Indicator: (3) Kinequip KML Lights LOCATION: (2) Amber & (1) Red lights, Inside, Over Rear Doors on Rear Header Pad	1
05-EL-43DL		Third (3rd) Brake Light: NONE	1
05-EL-4584		SCENE/FLOOD LIGHTS (LED-M9 Series)	1
05-EL-45L4		< /-- Left Scene Lights: (2) LED-M9, Chrome Flange Whelen Chrome Flange provided with purchase of Light.	1
05-EL-0224		/-- Flanges: Above M9 Scene lights, Incorporated into lights	1
06-EL-18LF		/-- Left Flood Activate: Left Flood Switch	1
05-EL-45T4		< /-- Right Scene Lights: (2) LED-M9, Chrome flange Whelen Chrome Flange provided with purchase of Light.	1
05-EL-0224		/-- Flanges: Above M9 Scene lights, Incorporated into lights	1
06-EL-18RT		/-- Right Flood Activate: Right Flood Switch and open CSE Door	1
05-EL-46R4		< /-- Rear Load Lights: (2) LED-M9, Chrome flange Whelen Chrome Flange provided with purchase of Light.	1
05-EL-0224		/-- Flanges: Above M9 Scene lights, Incorporated into lights	1
06-EL-18RE		/-- Activate: Rear Flood Switch, Reverse and Lead RA Door	1
06-EL-1800		/-- Add Activation: Rearward Left and Right scene lights. come on w/ Reverse	1
05-HA-0654	XS	< Secondary Heat/AC: Danhard 125VAC System, 50-3000 All underbody components must be mounted up high. With Danhard thermostat 50-2310 mounted in A/A Danhard Located in Squad Bench	1
05-HA-065J		< /-- Danhard Digital Thermostat remote mounted included Location:	1
05-HA-065L		/-- Danhard Compressor/ Condensor Mounted Underbody Forward of Axle	1
05-HA-13XF	S	HVAC SYSTEM: ACC Hepa-Max, Ducted in Ceiling - Above Talk-Thru Ford	1
05-HA-0406		/-- Water Pump: Installed required	1
05-HA-070X		/-- FILTER, Return Air: HEPA	1
05-HA-1306		/-- A/C Condenser: See M2 Cmpt for Condenser Information	1
05-HA-13X7		< /-- Intermotive Module Installed 2017+ F series Control of the Engine powered AC compressor clutch only	1
05-HA-14A0		/-- Side Plenum Grille, Return Air: Stamped Powder Coated Steel	1
05-HA-14C0		/-- AC COMPRESSOR: Tee into OEM	1
05-HA-14QX		/-- AC Evaporator: ACC (AC/Heat unit) w/ dual fans, "X" STD	1
05-HA-1404		/-- Heater Hoses: EPDM - Nomex Rubber (per Ford QVM)	1
05-HA-14A0		/-- Side Plenum Grille, Return Air: Stamped Powder Coated Steel	1
05-HA-14B1		/-- Filter, Washable Carbon Pre-Filter	1
10-HA-0304		< /-- Thermostat, Rear A/C, Digital, Class 1 LX-1, Includes Front Also Thermostat located in A/A as part of LX1 Multiplexed System	1
05-IL-00X1		< Ceiling Panels; white Aluminum Composite (2) piece X series MATL-CEILING	1
05-IL-01XR		< /-- Dome Lts, LED "LIGHT RAIL" system MTB NOTE: Requires X-Series Roof Structure design	1
05-IL-05T4	S	< /-- Check out Light Switch: Momentary For Multi-plex electrical systems. Part SWIT-C05  Located at head of squad bench on curbside wall  To power light rail at high intensity (15 minute timer)	1
05-IL-05T1		< /-- Timer, Constant Hot, Check out, Class 1 Multiplex System Activated with opening of either C/S or Rear Entry Doors.	1

PART NO	S	DESCRIPTION	QTY
06-EC-0914	<	-- 15 Minute Activation Light Circuit to stay on for 15 minutes when entry door is opened.	1
<b>06-EC-09P3</b>	<b>S</b>	<b> -- Timer to Power: Light Rail, High intensity</b>	<b>1</b>
<b>ZZ-ZZ-ZZZZ</b>		--	<b>1</b>
<b>09-MH-0801</b>		-- IV Hook No 1: CPI Rubber IV 2008-1(Recessed Mount), ILOS	<b>1</b>
<b>09-MH-08P3</b>		-- LOCATION: Over Knee/Waist area, primary patient on COT	<b>1</b>
<b>09-MH-0802</b>		-- IV Hook No 2: CPI Rubber IV 2008-1(Recessed Mount), ILOS	<b>1</b>
<b>09-MH-08P4</b>		-- LOCATION: Over Knee/Waist area, secondary patient on S/B	<b>1</b>
<b>09-MH-2AC6</b>	<	-- Recessed C/S Grab Rail, ceiling: 1.25 Dia..... 3 pt, 72in, Yellow Antimicrobial Grab Rail will be recessed in a ABS pan.	1
<b>09-MH-2AYX</b>	<	-- Recessed S/S Grab Rail, ceiling: 1.25 Dia..... 3 pt, 72in, Yellow Antimicrobial Grab Rail will be recessed in a ABS pan.	1
<b>Insulation PKG: X-Series units</b>			<b>1</b>
05-IN-3STX	<	-- Insulation: All Module Doors, 2" Black Foam, X-Series units #INSU-ARM2	1
05-IN-3STY	<	-- Insulation: All Module Doors, Black Sound Proofing, X-Series units #INSU-KSU	1
<b>05-IN-4ST9</b>	<	-- <b>Insulation Sound Deadening: Generation 9 Floor</b> Generation 9 Floor Design	<b>1</b>
05-IN-5STX	<	-- Insulation: Walls/Ceiling, 1" Black Foam, X-Series units #INSU-ARM1	1
05-IN-6STX	<	-- Stepwell Insulation: Urethane Froth Insulation, STD X-Series units MTB to spray urethane froth insulation, underside of step well area  MTB option #7208738	1
05-IN-6SXS	<	-- Black Sound Proofing, Doors & Select Walls, X-Series units INSU-KSU	1
05-IN-6SXT	<	-- Insulation: Circumferential PKG, 1LEF Reflective, X-Series units #KSU-F1250	1
<b>05-LB-6100</b>	<	-- <b>Light Bar Alternative, (4) Across Front, 92" or wider</b> In Addition to Standard Front Three (3) Body Warning Lights. Seven (7) Total Lights Across Front of Body.	<b>1</b>
<b>05-LB-6240</b>		-- <b>Front of Module M Series LED System - 92" and wider</b>	<b>1</b>
<b>05-LB-6615</b>		-- <b>Whelen M9, (2) Lights Color A, (2) Lights color B IATS</b>	<b>1</b>
<b>05-PM-LT03</b>		-- <b>Light: Whelen M9, LED, WHITE LED/CLEAR Lens, Programmable iats</b>	<b>2</b>
<b>05-PH-LF10</b>		-- <b>M9 Series Flange, Chrome Plated, Std. Each</b>	<b>2</b>
<b>25-PH-LT84</b>		-- <b>LED Lights: Programmable, Single Light</b>	<b>2</b>
<b>05-PM-LT07</b>		-- <b>Light: Whelen M9, LED, RED LED/RED Lens, Programmable IATS</b>	<b>2</b>
<b>05-PH-LF10</b>		-- <b>M9 Series Flange, Chrome Plated, Std. Each</b>	<b>2</b>
<b>05-PL-LY54</b>		-- <b>LED Color for Above M9 LED : RED</b>	<b>2</b>
<b>05-PM-LV20</b>		-- <b>Lens Color: Red</b>	<b>2</b>
<b>25-PH-LT84</b>		-- <b>LED Lights: Programmable, Single Light</b>	<b>2</b>
<b>05-LB-6900</b>		-- <b>Alternative Lightbar Switching, Prim/Sec</b>	<b>1</b>
05-PA-LB0B		-- Rear Light Bar: NONE	1
<b>05-PA-LB3A</b>	<	-- <b>Traffic Advisor: Whelen TAL85, (8) Amber 5mm Series LED lights, w/ TACTL5 cntrl</b> This is the LED Traffic Advisor Unit. Must be ordered with 25' to 30' Extension Cable.	<b>1</b>
<b>05-PA-LBM3</b>		-- <b>LOCATION: Mount over rear doors, below load lights</b>	<b>1</b>
<b>05-SY-LTMF</b>		<b>M SERIES LED WARNING LT SYSTEM - F-series LTD</b>	<b>1</b>

PART NO	S	DESCRIPTION	QTY
05-FS-0712		/-- Flasher: None, All M Series LED's Are Programmable	1
05-FS-10P4		/-- Flash Pattern: None, Internal Light Head Flasher	1
11-ZZ-0909	<	/-- CAAS GVS Exception to C.8.2.12 Warning lights non-compliant to Table 1 dual mode The Warning lights pattern chosen by the Customer does not meet either the required photometric output flash or the pattern required of Table 1, Dual mode, Primary Secondary of CAAS C.8.2.12. An exception has been taken for only this element to the standard.	1
06-SW-PS01		/-- Warning Light SWITCH: center console, Primary / Secondary	1
11-ZZ-0909	<	/-- CAAS GVS Exception to C.8.2.12 Warning lights non-compliant to Table 1 dual mode The Warning lights pattern chosen by the Customer does not meet either the required photometric output flash or the pattern required of Table 1, Dual mode, Primary Secondary of CAAS C.8.2.12. An exception has been taken for only this element to the standard.	1
ZE-00-0010	<	/-- Flash Pattern #1: SignalAlert This will be the Default Flash unless otherwise specified.	1
ZZ-ZZ-ZZZZ		/--	1
05-LB-8005	S <	/-- Opticom: 792H 3m Black/Gray Opticom Unit installed Strobe Infra-red Opticom, Stand Alone unit. EMIT-792H  Switch in Console. Only to Activate in Gear	1
05-LB-8121		/-- Opticom Location: Built into 600 Series Center Front Warning Light	1
ZZ-ZZ-ZZZZ		/--	1
ZZ-ZZ-ZZZZ		/--	1
05-PH-LSY5	S <	/-- (4) Grille Lights: Whelen M2, LED, Grille Lights to flash in an X pattern  Top Right and Bottom Left Program #1 Top Left and Bottom Right Program #2 Tie Gray Sync Wire Together	1
05-PH-LS0T		/-- Flanges: (2) Chrome, M2 Lights	2
05-PM-LRC7	S <	/-- Light: Whelen M2, LED, RED LED/RED Lens Programmable PAIR ILOS NOTE: BOTH Red on Driver side	1
05-PM-LV20		/-- Lens Color: Red	1
05-PM-LRCT	S <	/-- Light:s Whelen M2, LED, Green LED/Green Lens Programmable PAIR IATS Install a Chrome Flange LITE-M2FC (2) LITE-M2G (2)  NOTE: BOTH Green on PSGR side	1
05-PH-LA19		/-- Green LED	1
05-PM-LV50		/-- Lens Color: Green	1
05-PM-LE09		/-- (2) Intersection Lights: Whelen M2 Series, LED	1
05-PM-LN09		/-- Flanges,(2) Chrome : Intersection M2	1
05-PM-LRCJ	<	/-- Light: Whelen M2, LED, WHITE/RED LED/CLEAR Lens pair Programmable ILOS Set each color to steady burn and flash through the flasher system. White must flash opposite to the RED, unless specified otherwise.	1
05-FS-1212	S	/-- Programmable Lights Split Color	1
05-PM-LV10		/-- Lens Color: Clear	1
ZZ-ZZ-ZZZZ		/--	1
05-PH-LT31		/-- (1) Center Front CLEAR Warning Light: Whelen 600, HALOGEN	1
05-PH-LS0K		/-- Flange: (1) 600-Chrome Flanges for lights above	1
ZZ-ZZ-ZZZZ		/--	1
05-PM-LG70		/-- (2) Outer Front Body Lights: Whelen M9 Series, LED	1
05-PH-LF12		/-- M9 Series Flange Chrome Plated, Std: Pair	1
05-PM-LS24		/-- LED M9 Red - Pair	1

PART NO	S	DESCRIPTION	QTY
05-PM-LRK5		/-- Light: Whelen M9, LED, RED LED/RED Lens, Programmable ILOS	2
05-PL-LY54		/-- LED Color for Above M9 LED : RED	2
05-PM-LV20		/-- Lens Color: Red	2
25-PH-LT84		/-- LED Lights: Programmable, Single Light	2
ZZ-ZZ-ZZZZ		/--	1
05-PM-LH70		/-- (4) Upper Side Body Lights: Whelen M9 Series, LED	1
05-PH-LF14		/-- M9 Series Flange, Chrome Plated, Std: Two Pair	1
05-PM-LS44		/-- LED M9 Red - Two Pair	1
05-PM-LRK5		/-- Light: Whelen M9, LED, RED LED/RED Lens, Programmable ILOS	4
05-PL-LY54		/-- LED Color for Above M9 LED : RED	4
05-PM-LV20		/-- Lens Color: Red	4
25-PH-LT84		/-- LED Lights: Programmable, Single Light	4
05-PM-LI50		/-- (2) Rear Intersection Lights: Whelen M7 Series, LED	1
05-PH-LF22		/-- M7 Series Flange, Chrome Plated, Std: Each	2
05-PM-LR32		/-- LED M7 Red/White Split - Pair	1
05-PM-LRC1		/-- Light, Whelen LED M7 Red/White LED/Clear Lens - Programmable	2
05-FS-1212	S	/-- Programmable Lights Split Color	2
05-PL-LY12		/-- LED Color for Above M7 LED : RED/WHITE	2
05-PM-LV10		/-- Lens Color: Clear	2
05-PM-LJ70		/-- (2) Outer Rear Body Lights: Whelen M9 Series, LED	1
05-PH-LF12		/-- M9 Series Flange Chrome Plated, Std: Pair	1
05-PM-LS24		/-- LED M9 Red - Pair	1
05-PM-LRK5		/-- Light: Whelen M9, LED, RED LED/RED Lens, Programmable ILOS	2
05-PL-LY54		/-- LED Color for Above M9 LED : RED	2
05-PM-LV20		/-- Lens Color: Red	2
25-PH-LT84		/-- LED Lights: Programmable, Single Light	2
ZZ-ZZ-ZZZZ	S <	/-- Dimming Feature -programmed through LX-1 system	1
ALL Rear Body Lights shall automatically be dimmed, when the parking brake is applied.			
AEV will not dim the brake lights only the rear M9 warning lights will dim.			
There shall be a manual override switch to keep the rear lights in permanent dim mode.			
05-PM-LK80		/-- (4) Additional Rear Body Lights: Whelen M9 Series, LED	1
05-PH-LF14		/-- M9 Series Flange, Chrome Plated, Std: Two Pair	1
05-PM-LT07		/-- Light: Whelen M9, LED, RED LED/RED Lens, Programmable IATS	2
05-PH-LF10		/-- M9 Series Flange, Chrome Plated, Std. Each	2
05-PL-LY54		/-- LED Color for Above M9 LED : RED	2
05-PM-LV20		/-- Lens Color: Red	2
25-PH-LT84		/-- LED Lights: Programmable, Single Light	2
05-PM-LT07	S <	/-- Light: Whelen M9, LED, RED LED/RED Lens, Programmable IATS	2
LIGHTS SHALL STEADY BURN FOR BRAKES			
NOTE: Bottom two warning lights only to be brake light over ride when not in primary mode			
05-PH-LF10		/-- M9 Series Flange, Chrome Plated, Std. Each	2
05-PL-LY54		/-- LED Color for Above M9 LED : RED	2
05-PM-LV20		/-- Lens Color: Red	2
25-PH-LT84		/-- LED Lights: Programmable, Single Light	2
05-PM-LL30		/-- (1) Center Rear Body Light: Whelen M6 Series, LED ILOS	1
05-PH-LF20		/-- M6 Series Flange, Chrome Plated, Std: Each	1
05-PM-LQ06		/-- LED M6 Amber - Each	1
05-PM-LRG9		/-- Light: Whelen M6, LED, AMBER LED/AMBER Lens, Programmable	1
05-PL-LY40		/-- LED Color for Above M6 LED : AMBER	1
05-PM-LV40		/-- Lens Color: Amber	1
25-PH-LT84		/-- LED Lights: Programmable, Single Light	1
ZZ-ZZ-ZZZZ		/--	1
ZZ-ZZ-ZZZY		/--	1
ZZ-ZZ-ZZZZ		/--	1
05-ZZ-ZZZZ			1
ELECTRICAL - CELL 3			1
06-00-0005	S <	/-- Customer Supplied Part(s) : Yes See account	1
1) Stryker Power Load Cot Mount			
2) Knox Box Mini - Installed in I-2 of RF ALS			



PART NO	S	DESCRIPTION	QTY
		3) Keysecure 4 - Installed below the Talk Through Window between the Cab Seats	
		4) Cradle point WiFi System w/Router	
		5) Two SCBA BRACKETS	
07-00-0182		<i>/-- Custom design wood console included in Order</i>	1
06-00-0001			1
06-AL-47SU		Hand Held Spot Light: None	1
06-BA-3B40		<b>Batteries: 2 - Battery System - Type I Gasoline Chassis only</b>	1
06-BA-3F55		<i>/-- Batteries: (1) Underhood , (1) in M-8 (Type I Gasoline</i>	1
06-BA-3FE0	<	<i>/-- Battery Make: (2) 1 OEM +1 Ford Motorcraft BXT/65/750</i>	1
		One OEM battery under the hood OEM location	
		One additional battery at designated location,	
06-BA-3FM1		<i>/-- Batt Loc: (T3) (1) Underhood, Remainder Batt M-8</i>	1
06-BA-Q631	<	<i>/-- Battery Switch: Cole Hersee 2484-16 Paddle, T1 center console</i>	1
		Cole Hersee Paddle style battery switch powers up and shuts down the CONVERSION only! Chassis related circuits shall remain wired in the OEM configuration per Ford QVM Bulletin No 63.	
		SWITCH LOCATION: Drivers' side of center cab console.	
06-BA-3FW4		<i>/-- Batteries Wired: Parallel for higher amperage</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
06-EC-056C		POWER Door Locks: Module Doors, X-Series Units type 1 Ford	1
06-EC-050B	<	<i>/-- Door Locks, Tied into OEM System X series Type 1 Ford</i>	1
		Module power locks are tied to the Chassis power lock system	
		MDUL-BDLM506A Module door lock control F3/4/550	
06-EC-0512	<	<i>/-- OEM Key Fob: Included w/Chassis Unlock Mod Doors</i>	1
		Must also operate the Module Power Door Locks Optioned.	
06-EC-05B9		<i>/-- Door Lock Switches : Integrated in Interior Entry door Handles -x</i>	1
06-EC-05M0		<i>/-- ONLY the following doors shall have power door locks:</i>	1
06-EC-05X0		<i>/-- Electric Door Lock: (M-1A) Upper Left Front Compartment,</i>	1
06-EC-05X1		<i>/-- Electric Door Lock: (M-1) Left Front Compartment</i>	1
06-EC-05X2		<i>/-- Electric Door Lock: (M-2) Left Middle Compartment</i>	1
06-EC-05X4		<i>/-- Electric Door Lock: (M-3) Left Rear Compartment</i>	1
06-EC-05X6		<i>/-- Electric Door Lock: Rear Access Doors</i>	1
06-EC-05X7		<i>/-- Electric Door Lock: (M-5) Right Rear Compartment</i>	1
06-EC-05XA		<i>/-- Electric Door Lock: Curbside Access Door</i>	1
06-EC-05XB		<i>/-- Electric Door Lock: (M-7) Right Front Compt</i>	1
06-EC-081X	<	<i>/-- Remote Keypad #1: Installed, X-Series Units</i>	1
		MTB to cut mounting holes per provided drawing.	
06-EC-0816		<i>/-- Location: By Curbside Door</i>	1
06-EC-2800	<	<i>/-- Door Unlock Switch, Momentary, Exterior, hidden</i>	1
		NOTE: Installation of Remote Door Lock Switch feature may increase likelihood of unauthorized entry into vehicle. By checking this option, purchaser further agrees to hold REV or chassis manufacturer harmless for any loss of vehicle or contents caused by unlawful access.	
06-EC-0802		<i>/-- Location: Front Grille/Bumper Area</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
06-EC-3059	S	<i>/-- Camera View System - OEM Back Up Camera</i>	1
06-EC-4300		Back-up Alarm: Standard 102DB	1
06-EC-43B0		<i>/-- Cut Off Switch: Auto reset ,momentary style</i>	1
11-ZZ-0933	<	<i>/-- CAAS GVS V2.0 Exception C.16.1 Reset of Back-up Alarm</i>	1
		Installation of a reset of a back-up alarm shall cause an exception to the GVS 2.0 Standard for C.16.1 for this instance when a vehicle is shifted into reverse.	
06-EC-CCX2	S <	<b>Circuit Board, 12V: Multiplex LX1 F3/4/550 X-Series STD</b>	1
		Includes the Following Items, please add to order:	
		All the following need to be added as usual:	
		Rear Digital Thermostat/Control for A/C, includes front also	
		Door Open 15, minute check out timer for 15	



PART NO	S	DESCRIPTION	QTY
<b>Oxygen Contents Gauge front and back.</b>			
<b>(5) Minute Auto Battery Switch Shutdown (Kill Circuit)</b>			
06-EC-1304		-- Voltage Monitor, LX-1, w/ Warning Light	1
06-EC-2215		-- LX-1 Standard Module door Open Alarm and Icon on Front Display	1
06-EC-CB07		-- Circuit Protection, 12V: FET - Auto-reset	1
06-EC-SPA7		-- LX1 Main Switch Panel Location :	1
06-EC-SPA8		-- In Cab Console	1
06-EC-SPZ0		-- Patient Area LX1 Panel:	1
06-EC-SPZ1		-- Pt Area LX1 Switch Panel: One Standard In Patient Compartment	1
06-EC-SPA1		-- Switch Panel Located: Streetside A/A	1
06-EC-SP70		-- Patient area switch panel mounted :flat to action wall std	1
06-FS-1106		-- Sequencer, LX1, with load manager,	1
06-RR-240X		-- Type I - CAB Wood Console: Pass Thru - 14" OAW Standard.	1
07-RR-24A0		-- Console Finish: Black, Textured "Easy Grip"	1
<b>07-RR-020F</b>	<b>S &lt;</b>	-- <b>Add-on Console: Type 1</b>	<b>1</b>
<b>UPDATED CONSOLE DRAWING NEEDED FROM ENGINEERING W/125 OUTLET ADDED</b>			
<b>07-RR-02A0</b>		-- <b>Drink Holder: (2) In Add-on Console, Big Gulp Size</b>	<b>2</b>
<b>07-RR-02A5</b>		-- <b>Drink Holder Location: Front</b>	<b>2</b>
<b>07-RR-02E0</b>		-- <b>Note Book Slot: Single - Full width by 4" wide</b>	<b>1</b>
<b>07-RR-02F2</b>		-- <b>(1) Removable Lexan Divider(s)</b>	<b>1</b>
<b>07-RR-2301</b>		-- <b>Customer Radio: Space for Customer installed Radio Heads</b>	<b>1</b>
<b>07-RR-24A0</b>		-- <b>Console Finish: Black, Textured "Easy Grip"</b>	<b>1</b>
<b>07-ZZ-ZZZZ</b>		--	<b>1</b>
07-ZZ-ZZZZ		--	1
06-EC-GR01		Ground Straps, Module to Frame: (Qty 4) Braided	1
06-IA-0001		Converter , 125V to 12V: NONE	1
<b>06-IG-0310</b>		<b>Inverter : Vanner 20-1050 CUL-DC - Full Mod</b>	<b>1</b>
<b>06-EC-03AS</b>		-- <b>Portable Equip Charging Circuits: Included in Inverter</b>	<b>1</b>
<b>06-EC-03AA</b>		-- <b>PREWIRE LOCATION: (1)Cab Console, (1) Behind A/A</b>	<b>1</b>
<b>06-EC-03C9</b>	<b>&lt;</b>	-- <b>Portable Equip Pwr Source: Ignition and/or Shoreline</b>	<b>1</b>
<b>Reference 3.7.7.2 and Figure 7 in KKK-A-1822E</b>			
<b>06-IG-03A0</b>		-- <b>Battery Charger/Conditioner: 55A - Built into Inverter</b>	<b>1</b>
<b>06-IG-0003</b>		-- <b>Built-in Battery Charger: Enable - Wire to Batteries</b>	<b>1</b>
<b>06-IG-04L7</b>		-- <b>Inverter Location: M-1A (ULF) Compartment</b>	<b>1</b>
06-MC-0901		Low Voltage Buzzer: Installed, Multiplex units	1
<b>COMMUNICATION RADIO(S) RELATED</b>			<b>1</b>
06-00-0001		--	1
<b>RADIO POWER</b>			<b>1</b>
06-EC-03A0		-- Radio Power No 1: 30A, Pos and Neg, 10 awg Wires	1
<b>06-EC-03C0</b>		-- <b>Radio Power Source: Battery (Constant) Hot</b>	<b>1</b>
<b>06-EC-03J0</b>		-- <b>LOCATION: Inside Cab Center Console</b>	<b>1</b>
06-EC-03A2		-- Radio Power No 2: 30A, Pos and Neg, 10 awg Wires	1
<b>06-EC-03C0</b>		-- <b>Radio Power Source: Battery (Constant) Hot</b>	<b>1</b>
<b>06-EC-03J0</b>		-- <b>LOCATION: Inside Cab Center Console</b>	<b>1</b>
<b>06-EC-03A3</b>		-- <b>Radio Power No 3: 30A, Pos and Neg, 10 awg Wires</b>	<b>1</b>
<b>06-EC-03C0</b>		-- <b>Radio Power Source: Battery (Constant) Hot</b>	<b>1</b>
<b>06-EC-03E0</b>		-- <b>LOCATION: Behind Action Area Board</b>	<b>1</b>
<b>ANTENNA LEADS</b>			<b>1</b>
<b>06-RR-1710</b>	<b>&lt;</b>	-- <b>Antenna Base w/ Coaxial Cable: KE794 #1</b>	<b>1</b>
<b>MOUN-KE794</b>			
<b>06-RR-1760</b>	<b>&lt;</b>	-- <b>Roof Location: Roof Port #1</b>	<b>1</b>
<b>MOUN-K794</b>			
<b>Line up with edge of curbside entry door, centered side to side as near as possible.</b>			
<b>06-RR-1772</b>	<b>&lt;</b>	-- <b>Termination Point: Inside Center Console</b>	<b>1</b>
<b>MOUN-K794</b>			

PART NO	S	DESCRIPTION	QTY
06-RR-1712	<	/-- Antenna Base w/ Coaxial Cable: KE794 #2 MOUN-KE794	1
06-RR-0102	<	/-- ORIGINATION POINT: Roof Port No 2 Roof Port No 2 is located approximately 24 inches back rearward of roof port #1.	1
06-RR-01P0		/-- Port Plate: None - Access thru center upholstery panel	1
06-RR-1772	<	/-- Termination Point: Inside Center Console MOUN-K794	1
06-RR-1714	<	/-- Antenna Base w/ Coaxial Cable: KE794 #3 MOUN-KE794	1
06-RR-0103	<	/-- ORIGINATION POINT: Roof Port No 3 Roof Port No 3 is located approximately 24 inches back rearward of roof port #2.	1
06-RR-01P0		/-- Port Plate: None - Access thru center upholstery panel	1
06-RR-1774	<	/-- Termination Point: Behind A/A Board MOUN-K794	1
06-RR-1100	S <	/-- Antenna, Customer Supplied prior to production, Installed To be installed with/for Cradle Point WiFi System  This antenna is to be mounted to the box roof and terminated electrical storage compartment H	1
06-RR-1809		/-- Patient Area Radio : None	1
06-SO-0000		125V SHORE LINE AND OUTLETS	1
06-00-0001	/--		1
06-SO-0500		/-- Shore Line Inlet: 20A Super Auto Eject, ILOS	1
06-SO-00L1		/-- Inlet location: Aft of Left Front compartment	1
06-SO-0801	<	/-- Indicator Light, Shore line: Weather proof, power by SL, Green Indicator light located above shore line inlet.	1
06-SO-1010		/-- Cover, White, Shore Line Inlet : 20A Super Auto Eject, ILOS	1
ZZ-ZZ-ZZZZ	/--		1
06-SO-10TT	<	/-- Inpower Timer: VCM-05-01SF, Installed NOTE: This allows the auto eject to be wired to the ignition switch In lieu of splicing into the OEM starter circuit and is required any this vehicle	1
06-SO-0400		/-- Shore Line Inlet No 2: 20A Super Auto Eject, IATS	1
06-SO-00L2		/-- Inlet location (IATS): Above M-2, Aft of M-1 compartment	1
06-SO-0801	<	/-- Indicator Light, Shore line: Weather proof, power by SL, Green Indicator light located above shore line inlet.	1
06-SO-1020		/-- Cover, Blue, Shore Line Inlet : 20A Super Auto Eject, ILOS	1
ZZ-ZZ-ZZZZ	/--		1
06-SO-1400	/--	**125 Volt OUTLETS**	1
06-SO-1401	<	/-- 125 VAC Outlet, No 1: 15A, Hospital Grade, IVORY All 125 VAC outlets shall be back lighted when power is applied to the outlet.	1
06-SO-14L1		/-- LOCATION: Action Area, standard location	1
06-SO-1402		/-- Outlet mounting ORIENTATION: Vertical	1
ZZ-ZZ-ZZZZ	/--		1
06-SO-1402	/--	125 VAC Outlet, No 2: 15A, Hospital Grade, IVORY	1
06-SO-14L3	/--	LOCATION: RF ALS, (See Drawing)	1
06-SO-1402	/--	Outlet mounting ORIENTATION: Vertical	1
ZZ-ZZ-ZZZZ	/--		1

PART NO	S	DESCRIPTION	QTY
06-SO-1403		/-- 125 VAC Outlet, No 3: 15A, Hospital Grade, IVORY	1
06-SO-14L4	S	/-- LOCATION: FORWARD OF CPR SEAT, (See Drawing)	1
06-SO-1402		/-- Outlet mounting ORIENTATION: Vertical	1
ZZ-ZZ-ZZZZ		/--	1
06-SO-1404		/-- 125 VAC Outlet, No 4: 15A, Hospital Grade, IVORY	1
06-SO-14L4	S	/-- LOCATION: Front of Console Perpendicular to the Dash	1
06-SO-1402	S	/-- Outlet mounting ORIENTATION: Horizontal	1
ZZ-ZZ-ZZZZ		/--	1
06-SO-1100		**INTERIOR 12 Volt OUTLETS**	1
06-SO-1101		/-- 12V Outlet, No 1: Power Point Double Outlet- Wire thru Med Isolator	1
06-SO-11L1		/-- LOCATION: Action Area, standard location	1
06-SO-1402		/-- Outlet mounting ORIENTATION: Vertical	1
06-SO-1910		/-- Power Source: Medical Isolator , Batt Sw Hot	1
ZZ-ZZ-ZZZZ		/--	1
06-SO-1103		/-- 12V Outlet, No 3: Power Point - Wire thru Med Isolator	1
06-SO-11L3	S <	/-- LOCATION: RF ALS, Drawer I-2 A (See Drawing) In Drawer I-2a of RF ALS for IV Warmer Needs to be in a Weather Proof Box	1
06-SO-1402		/-- Outlet mounting ORIENTATION: Vertical	1
06-SO-1913		/-- Power Source: The SAME as outlet No 1	1
ZZ-ZZ-ZZZZ		/--	1
06-SO-1104	S	/-- 12V Pre-wire No 1:	1
06-SO-11L3	S <	/-- LOCATION: Special Location For Cradlepoint Wifi System.	1
		To be installed with/for Cradle Point WiFi System	
		This antenna is to be mounted to the box roof and electrical storage compartment H	
06-SO-1402		/-- Outlet mounting ORIENTATION: Vertical	1
06-SO-1913	S	/-- Power Source: (CONSTANT HOT)	1
ZZ-ZZ-ZZZZ		/--	1
06-SO-1105	S	/-- 12V Pre-wire No 2:	1
06-SO-11L4	S <	/-- LOCATION: Special Location In Cab between seats for a Keysecure 4	1
06-SO-1402		/-- Outlet mounting ORIENTATION: Vertical	1
06-SO-1913	S	/-- Power Source: Ignition Hot	1
ZZ-ZZ-ZZZZ		/--	1
06-SO-1106	S	/-- 12V Pre-wire No 3:	1
06-SO-11L4	S <	/-- LOCATION: Special Location I-2 of RF ALS for Knox Box Mini	1
06-SO-1402		/-- Outlet mounting ORIENTATION: Vertical	1
06-SO-1914	S	/-- Power Source:(CONSTANT) Hot	1
ZZ-ZZ-ZZZZ		/--	1
06-SO-1108	S	/-- 12V Pre-wire No 4:	1
06-SO-11L4	S <	/-- LOCATION: Special Location In Cab Center Console	1
06-SO-1402		/-- Outlet mounting ORIENTATION: Vertical	1
06-SO-1914	S	/-- Power Source:(CONSTANT) Hot	1
ZZ-ZZ-ZZZZ		/--	1
06-SS-020A		Siren: Federal, EQ2B, F-Series, ILOS	1
06-SS-DF00	<	/-- Siren Speakers: Federal # ES100-ESMFT-EF, Ford F-350/450/550 2017 ILOS These speakers require a recessed mount requiring a hole in the outer end of the front bumper. SPEA-ES100ESMFT	1
06-SS-SW01	<	/-- Siren / Horn Switch: In Cab Console Siren Functions OR OEM Horn	1
06-SS-SW04		/-- microphone clip not installed Tie to Siren Microphone cord.	1

PART NO	S	DESCRIPTION	QTY
06-SS-1313		Air Horn System: BUELL - F1	1
06-SS-1304	S	/-- Air Horns ACTIVATION: White Rocker Switch in Console	1
06-SS-1305		/-- Air Tank Mounted to Frame Rail	1
06-SS-1310		/-- Emergency Master Hot	1
06-SS-1340		/-- Compressor: Buell #6540, 20% Oil less Intermittent Duty	1
06-SS-1347		/-- Compressor Location: M-1A Compartment	1
06-SS-13F2	<	/-- Air Horn Location: Under Front Bumper, F-450 and F-550 2017 + For F-550 may require recess cut into ABS valance - Air Dam.	1
06-SS-1321		/-- Left Air Horn: 10" Buel Strombos Horn, Chrome, No 1061 (493 Hz)	1
06-SS-1332	<	/-- Right Air Horn: 12" Strombos Horn, Chrome, No 1062 (396 Hz) HORN-04	1
06-SS-13M0	<	/-- Air horn mounted system Standard chrome finish no adjustments to system	2
CABINET SHOP - Modular			1
07-00-0182		/-- Custom design wood console included in Order	1
ZZ-ZZ-ZZZZ		/--	1
07-00-0001	<	ALL DIMENSIONS ON ORDER WILL HAVE A VARIABLE OF + OR - 1/4" Unless specified as a minimum dimension.	1
ZZ-ZZ-ZZZZ		/--	1
***Aluminum Composite Cabinet Configuration 172 Type 1			1
07-00-0006		/-- Rubber Cactus Mat : On Cabinet Floors, Drawers & Shelves, X-Series units	1
07-00-0030	<	/-- Aluminum Cabinet Backer-Sound Barrier # INSU-KSU on back side of aluminum cabinets	1
07-00-MB90		/-- Interior Color Packages	1
07-00-MC01		/-- Mica Color: Matte Gray D355-60	1
07-00-N002	S	/-- All Cabinet interiors: White Anti-Microbial Powder Coated	1
ZZ-ZZ-ZZZZ		/--	1
07-00-PC0P	<	/-- Polycarbonate Type/Color: Lexan - Gray Secure Latch Note; For any secure latch window requested where a cabinet opening width is 20 inches or less, the secure latch window will be questioned at ordering.	1
07-00-PH01		/-- Window Handles: Full Length Extruded	1
11-SX-0335	S <	/-- Att Seat, EVS #1880 Child Safety Seat Dove W/ Per4max Black Belt X-ILOS Vacuum formed Dove Gray Per4Max Seat belt Black slide track. recessed Child safety Belt Black	1
07-SE-0901	<	/-- BASE: Swivel base for EVS Child Seat Option Handle on RIGHT std (2) Position Swivel, Forward or Rearward, Only BASE-1882S EVS handle is on right.	1
11-SE-04A0		/-- Attendant Seat, Armrest: None	1
ZZ-ZZ-ZZZZ		/--	1
07-AC-4500	S <	/-- AC CABINET: Evaporator, Location : Bulkhead X Series STD composite Over Talkthru Composite Construction	1
07-ZZ-ZZZZ		/--	1
07-CA-03XA		/-- CURBSIDE UPPER: Over Squad Bench	1
07-CU-X107		/-- Cabinet K1 & K2: (2) Openings with flush center divider	1
07-DR-LXX2		/-- (K) Door: Single Flip Up 3/8" Lexan	2
07-DR-LZ20		/-- Hinges: Reel Torque	2
07-HW-SO11		/-- Round Pull Latch: Non-locking - Chrome Finish	2
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	2
07-ZZ-ZZZZ		/--	1
07-CA-04A9	S	/-- Cabinet, (3) Glove Storage, over Rear Entry Doors	1

PART NO	S	DESCRIPTION	QTY
07-DR-LX04		/-- Door: Overlay He, 3/8" Lexan - 3-glove dispense thru	1
07-HW-SO11		/-- Round Pull Latch: Non-locking - Chrome Finish	1
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	1
07-ZZ-ZZZZ		/--	1
07-CA-04B0		/-- CURBSIDE REAR STORAGE CABINET: NONE	1
07-ZZ-ZZZZ		/--	1
07-LF-4500		/-- LF Cabinet, Behind Att Seat: Cabinet "H" X Series Aluminum/ Composite	1
07-DR-WDX1		/-- Door, Single Solid, Flush Fitted	1
07-CA-2100		/-- TRIM: U-shaped Door, J-trim opening	1
07-CA-VEN7		/-- Plastic Vent: (2) Total, 1 column x 8 row, Vent 01	1
07-DR-OR04		/-- Hinge Orientation: RIGHT	1
07-HW-HIN1		/-- Hinge: 1 1/2" Stainless Steel Piano Hinge	1
07-HW-SX11		/-- Round Pull Latch: Non-locking - Chrome Finish	1
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	1
07-RF-4500	<	/-- RF ALS Cabinet: Aluminum Composite Construction X-Series Design with 45°	1
07-CA-04AX		/-- Cabinet, (3) Glove Storage, 45° Section of RF ALS cabinet, X-Series	1
07-DR-LX0C		/-- Door: Overlay Hinged, 3/8" Lexan - 3-glove dispense thru X-SERIES	1
07-DR-LZ10		/-- Hinges: Stainless Spring Loaded	2
07-HW-SX11		/-- Round Pull Latch: Non-locking - Chrome Finish	1
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	1
07-RF-0003	S	/-- Interior Color: White Anti-Microbial Powder Coated	1
07-RF-11X1	S	/-- Cabinet I-1: Delete/Combine with I-2	1
07-ZZ-ZZZZ		/--	1
07-RF-12X1	S <	/-- Cabinet I-2: Shortened for Drawer Option Customer supplied Knox Box to be mounted on the bottom of the I-2 area near wall #1 toward the front of the als. To be mounted inside of an aluminum cabinet. Ref Dwg.	1
07-CA-3300	XS <	/-- Door, Roll up, ROM, I-2 Secion of ALS Compliant Satin aluminum finish Lower Key lock Lower bar latch installed >> Cabinet design engineering to complete measurement sheet and submit to BOM team for ordering <<  Roll Up to Cover I-2 Only	1
11-X0-0020		/-- Stowage rating label - Robinson ROM Roll up Door 80 pounds entire area	1
07-RA-IOA1		/-- Outside Access: Thru M-7 (RF) Compartment door.	1
07-RF-0001	S	/-- Interior Color: White Anti-Microbial Powder Coated	1
07-TS-12X2		/-- Shelf Track: Small Alum. Unistrut, X-Series, RF ALS cabinet	1
07-CA-06VD	S	/-- (1) Shelf: Adjustable, Aluminum, White Anti-Microbial coated, STD	1
07-TZ-I26A	S	/-- Drawer I-2A: 6" high Aluminum Composite	1
07-DR-WD14		/-- Drawer Front: Flush Fitted	1
07-CA-2100		/-- TRIM: U-shaped Door, J-trim opening	1
07-HW-SO12	S	/-- Round Pull Latch: Locking - Chrome Finish	1
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	1
07-HW-SL01		/-- Drawer Slides: Full Extension, Detachable 130 LB capacity STD	1
07-RF-0001	S	/-- Interior Color: White Anti-Microbial Powder Coated	1
07-TZ-I26X	S	/-- Drawer I-2B: Aluminum Composite	1
07-DR-LXXF		/-- (i) Drawer Front: Flush Fitted	1
07-CA-2100		/-- TRIM: U-shaped Door, J-trim opening	1
07-HW-SX11		/-- Round Pull Latch: Non-locking - Chrome Finish	1
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	1
07-HW-SL01		/-- Drawer Slides: Full Extension, Detachable 130 LB capacity STD	1
07-RF-0003		/-- Interior Color: White Anti-Microbial Powder Coated	1
07-XA-3800	S <	/-- Dividers, (4) Adj 3/16" Lexan w/ ABS slotted track - EA cab (4) dividers to run front to back in I-2B Drawer	1
ZZ-ZZ-ZZZZ		/--	1
07-RF-I3X0	S	/-- Cabinet I-3: Aluminum Composite	1
07-DR-LXX7		/-- Doors Dual, Overlay Hinged, 3/8" Lexan - Large Cabinet	1



PART NO	S	DESCRIPTION	QTY
07-DR-LZ10		/-- Hinges: Stainless Spring Loaded	1
07-HW-SO11	S	/-- Round Pull Latch: Non-locking - Chrome Finish	2
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	2
07-RA-IOA1		/-- Outside Access: Thru M-7 (RF) Compartment door.	1
07-RF-0001	S	/-- Interior Color: White Anti-Microbial Powder Coated	1
07-TS-12X2		/-- Shelf Track: Small Alum. Unistrut, X-Series, RF ALS cabinet	1
07-CA-06VD	S	/-- (1) Shelf: Adjustable, Aluminum, White Anti-Microbial coated, STD	1
07-ZZ-ZZZZ		/--	1
07-RR-0064		/-- Right Rear Cabinet: Cover over M-5 Compartment	1
07-RR-0364	<	/-- Inside access into M-5: Face Aisle The inside access opening shall positioned on the forward half of M-5 compartment. The clear opening shall be 8" wide by 32" tall. IF SPECIAL SIZE opening is required, please define; _____ " W x _____ " Tall	1
07-DR-WD00		/-- Door, Single Solid, Flush Fitted	1
07-CA-2100		/-- TRIM: U-shaped Door, J-trim opening	1
07-DR-OR04		/-- Hinge Orientation: RIGHT	1
07-HW-HIN1		/-- Hinge: 1 1/2" Stainless Steel Piano Hinge	1
07-HW-SO11	S	/-- Round Pull Latch: Non-locking - Chrome Finish	1
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	1
07-ZZ-ZZZZ		/--	1
07-ZZ-ZZZZ		/--	1
07-SA-0000		/--	1
07-SB-4500	S <	/-- SQUAD BENCH: Aluminum Composite Construction X Series NOTE: SQUAD BENCH PAD WILL BE FULL LENGTH OF THE SQUAD BENCH	1
07-SB-0001		/-- See Upholstery Section for Post and Wheel Cup info	1
07-SB-1102	S <	/-- Bio-waste/Sharps No 1: Roll-out DRAWER (164) This Option is in lieu of Standard Bio-waste, normally located in the Action Area. This is the primary Bio-waste receptacle.  NOTE: Sharps in Front and Trash in Rear of Drawer	1
07-SB-0998		/-- LOCATION: At head of Squad Bench, Roll out toward aisle	1
07-SB-1005		/-- WASTE CONTAINER: 6 Quart	1
07-SB-1008		/-- SHARPS CONTAINER: 2-Gallon Sharps-A-Gator (CONT-02)	1
ZZ-ZZ-ZZZZ		/--	1
07-SB-1001	S	/-- Storage Under Lid	1
07-SB-LIDX		/-- Squad Bench Lids: Split - 2-section	1
07-SB-LH00		/-- Hinge, Squad Bench Lid(s): Butt Style Hinges	1
07-SB-LH03		/-- Lid Checks: Gas shock, Dual Action	2
07-SB-LH07		/-- Latch, Squad Bench Lid: Slam Action Paddle, W keeper	2
11-X0-0030		/-- Stowage rating label - Squad bench interior, entire area 80 lbs	2
07-TR-SB01		/-- Edge Trim, Lids: Band w/ Laminate and J-Trim Protection	1
ZZ-ZZ-ZZZZ		/--	1
08-MH-1404		/-- Restraint Net, at head of S/B, NONE	1
08-ZZ-ZZZZ		/--	1
09-MH-1AC5	<	/-- Bio-Waste 16" A-Bar, SS Removable, Model #V7544SS (No Biowaste) Part; ABAR-V7544SS Stainless A-Shaped Bar installed at head of squad bench, NO BIOWASTE	1
07-TC-4500	S	/-- TOP CABINETS, - w/ 74" HR, Aluminum Composite Construction X STD	1
07-TC-A450	S	/-- Cabinet A & D Combined: 74" HR Aluminum Composite X std	1
07-CB-DR71	S <	/-- Doors; Cabinet Secure Latch Restocking Sliding Window Top hinged Optional upgrade	1
11-X0-0016		/-- Stowage rating label Secure Latch Restocking Sliding Window 30 pounds applied	1
07-TS-12X0		/-- Shelf Track: Small Alum. Unistrut, X-Series	1
07-CA-06VB		/-- (1) Shelf: Adjustable, Aluminum, White Anti-Microbial coated	1
07-ZZ-ZZZZ		/--	1
07-TC-B450	S	/-- Cabinet B1 & B2: Economically angled toward the CPR seat (74"HR) X Std	1
07-CB-DR75	S	/-- Doors; Cabinet B1 & B2 Secure Latch Restocking Sliding Window Top hinged x	2



PART NO	S	DESCRIPTION	QTY
11-X0-0016		/-- Stowage rating label Secure Latch Restocking Sliding Window 30 pounds applied	2
07-TS-12X0		/-- Shelf Track: Small Alum. Unistrut, X-Series	1
07-CA-06VB		/-- (1) Shelf: Adjustable, Aluminum, White Anti-Microbial coated	1
07-ZZ-ZZZZ		/--	1
07-WC-0000		/--	1
07-WC-4500	S	/-- WALL CABINET: CPR Seat w/NO Telemetry, Aluminum Composite Construction X	1
07-WC-AAX1	S	/-- Action Area: EXTENDED	1
07-CA-4500	<	/-- Writing Tray, Slide out, in face of A/A Install Pull Strap on Tray	1
11-YZ-0907	<	/-- Non-Compliant to 3.11.3 J3058, cabinets shall not come open in transit Item is not tested to J3058, or not rated.	1
07-CA-480V	<	/-- 1/2" Solid Surface A/A Tray No Bio Waste, X-Series ILOS No sharps or trash cutouts requested.	1
07-CA-4812		/-- (Solid Surface) Material COLOR: Light Beige Mirage 1531 MG	1
07-WC-AABD		/-- Action Area Board: Black Grip See Station No 6 for content	1
07-ZZ-ZZZZ		/--	1
07-WC-F64Y	S	/-- (2) Drawers under Action Area: Aluminum Composite Construction	2
07-HW-SX12	S	/-- Round Pull Latch: Locking - Chrome Finish	2
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	2
07-ZZ-ZZZZ		/--	2
07-ZZ-ZZZZ		/--	1
07-WC-O10X	S	/-- CUSTOM Cabinet Storage: - Open Storage, under Action Area (See Drawing)	1
07-CB-DR00		/-- Open Cabinet: No Door, Trim Opening	1
07-CB-DR03		/-- Trim Type: J-Trim	1
07-RF-0002		/-- Interior Material and Color: To be Color Keyed Laminate	1
11-YZ-0907	<	/-- Non-Compliant to 3.11.3 J3058, cabinets shall not come open in transit Item is not tested to J3058, or not rated.	1
ZZ-ZZ-ZZZZ		/--	1
07-WC-O10X	X	/-- Cabinet O1: DELETE	1
07-WC-X301	S	/-- Aluminum Cabinet Configuration:	1
07-WC-C64X		/-- Cabinet C: Aluminum Composite Construction	1
07-CB-DR7D	S <	/-- Doors; Cabinet C Secure Latch Restocking Sliding Window Top hinged x (1) WIND-CFTG	1
11-X0-0016		/-- Stowage rating label Secure Latch Restocking Sliding Window 30 pounds applied	1
07-RF-0008		/-- No Inside Access To Exterior Compartment	1
07-TS-12X0		/-- Shelf Track: Small Alum. Unistrut, X-Series	1
07-CA-06VB		/-- (1) Shelf: Adjustable, Aluminum, White Anti-Microbial coated	1
07-ZZ-ZZZZ		/--	1
07-WC-D003	S	/-- Cabinet D: DELETE - COMBINED WITH CABINET A	1
07-ZZ-ZZZZ		/--	1
07-WC-E64X	S <	/-- Cabinet G: 172 Standard, Aluminum Composite Construction Below Action Area forward of Open Storage and Writing Tray	1
07-CB-DR46	S	/-- Doors; Cabinet G Secure Latch Sliding Window	1
11-X0-0014		/-- Stowage rating label - Secure Latch Sliding Window 40 pounds applied each	1
07-ZZ-ZZZZ		/--	1
07-WC-E64X	X	/-- Cabinet E: DELETE	1
07-WC-F64Y	S <	/-- Drawer F1: Aluminum Composite Construction LOCATED FORWARD FORWARD OF THE CPR SEAT AND REARWARD OF THE ACTION AREA.	1
07-HW-SX11		/-- Round Pull Latch: Non-locking - Chrome Finish	1
11-X0-0010		/-- Stowage rating label - Southco round latch 10 pounds applied each	1

PART NO	S	DESCRIPTION	QTY
07-SB-1022	S	<b>/-- Cabinet F2: Bio-waste/Sharps No 1: (1) Tilt-out Door (Wall cabinet)</b>	1
07-HW-SO11	S	<b>/-- Round Pull Latch: Non-locking - Chrome Finish</b>	1
11-X0-0010		<b>/-- Stowage rating label - Southco round latch 10 pounds applied each</b>	1
07-SB-1015	S <	<b>/-- WASTE CONTAINER: 2-Gallon (#CONT-311)</b>	1
		CONT-311	
07-SB-1023	S	<b>/-- LOCATION: Wall Cabinet, Forward of CPR seat</b>	1
07-SB-1024	<	<b>/-- SHARPS CONTAINER: Wlth bracket -185, 1.7 quart</b>	1
		CONT-185	
07-ZZ-ZZZZ		<b>/--</b>	1
07-WC-SS02	S <	<b>/-- Side Seat: 24" - Single Position - Under Lid Storage w/Latch</b>	1
		CPR SEAT MOVED REARWARD TOWARD THE M-3 FILLER/CABINET C AS MUCH AS POSSIBLE.	
07-WC-BA00		<b>/-- Hinge, CPR Seat Lid(s): Butt Style Hinges</b>	1
07-WC-BR01		<b>/-- Back Rest: Fixed to Back Wall of CPR Seat w/clips</b>	1
ZZ-ZZ-ZZZZ		<b>/--</b>	1
07-WC-TAX1	S	<b>/-- Telemetry Area: NONE/DELETE</b>	1
ZZ-ZZ-ZZZZ		<b>/--</b>	1
08-SE-1702		<b>/-- P4 - 4-Point PER4MAX Restraint System - with replacement indicator W/CPR</b>	1
08-SE-1847	<	<b>/-- (2)Per4max above Squad Bench, (1) Per4Max above CPR Side Seat Black Belts</b>	1
		Belt retractors can mount above the seat level,	
08-SE-SB70		<b>/-- S/B: (3) Sec patient restraints - 9" Sleeves Face of Bench</b>	1
08-SE-SB76		<b>/-- S/B: (3) Sec patient restraints - 5" Sleeves By Hinge</b>	1
00-20-0072		<b>/-- Per4Max Four-Point Seatbelts: Accept and Install Full Feature</b>	1
ZZ-ZZ-ZZZZ		<b>/--</b>	1
ZZ-ZZ-ZZZZ		<b>/--</b>	1
07-ZZ-ZZZZ		<b>/--</b>	1
		<b>CABINET SET - CELL 4 - MOD</b>	1
08-00-00CX		<b>/-- Sub Floor, 3/4" Composite, STD</b>	1
ZZ-ZZ-ZZZZ		<b>/--</b>	1
08-00-FL3A		<b>Flooring: Loncoin II Flecks- #150, Onyx (Black)</b>	1
08-00-FL01		<b>/-- Flooring Main Edge: 3" Recessed (1/2" deep) roll-up</b>	1
08-AS-0005		<b>/-- Rear Threshold, Covered with Yellow Speedliner 6" W x Full W at rear doors</b>	1
08-AS-0007		<b>/-- C/S Stepwell Threshold, Yellow Speedliner Covered Smooth Aluminum</b>	1
ZZ-ZZ-ZZZZ		<b>/--</b>	1
08-ZZ-ZZZZ		<b>/--</b>	1
08-CS-0001		<b>COT MOUNT HARDWARE: (Full Size Mod)</b>	1
08-CR-09PS	<	<b>/-- Cot Mount: Stryker, No 6390, Power Load, CUST/DLR SUP -MOD option.</b>	1
		Install Customer/Dealer supplied Stryker #6390 Power Load system complete with mechanical fasteners as required and electrical connections with testing. Manuf. supplies only the floor cut out by CNC machine and 12v wiring from main electrical system and installation.	
		>>> Caution, Power load head consumes floor space toward attendant seat. Spacing review between seat and cot is recommended. >>	
08-CR-09PN		<b>/-- mass casualty kit not requested</b>	1
08-CR-09SM		<b>/-- No Bolt On Stryker Antler Required.</b>	1
08-CR-1002	<	<b>/-- 12v power feed location FRONT for Stryker power load 6390</b>	1
		The 12 volt feed will be drilled and fed through the template FRONT hole for a Stryker power load system. The 12volt power shall be brought through the floor, with Heat shrink connectors installed.	
08-CS-00PL	<	<b>/-- Cot Position No 1: PRIMARY CENTER POSITION, Maintain 12" between Cot and S/B.</b>	1
08-CS-2000	<	<b>/-- Primary Cot position under floor reinforcement</b>	1
		Install 8 inch wide by 5 long 1/2" aluminum reinforcement at primary cot position. (Primary cot position only - REV Std)	
		**If custom location is desired, must be specified below.	

PART NO	S	DESCRIPTION	QTY
08-CS-3009		<i>/-- Cot mount set up for: Stryker Power-Pro 6506</i>	1
08-CS-19A5		<i>/-- Cot Stop, Block: Stryker Power/Performance load. Install hook with kit</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
08-CS-19U1		<i>/-- Q Straint System: NONE</i>	1
08-OS-04SX		OXYGEN / AIR / VACUUM System: X-Series	1
08-OS-0401		<i>/-- Oxygen Outlet No 1: Amico Console - Ohmeda/Ohio Diamond Style</i>	1
08-OS-040A		<i>/-- LOCATION: Action Area</i>	1
08-OS-0402		<i>/-- Oxygen Outlet No 2: Amico Console - Ohmeda/Ohio Diamond Style</i>	1
08-OS-040A		<i>/-- LOCATION: Action Area</i>	1
08-OS-0403		<i>/-- Oxygen Outlet No 3: Amico Console - Ohmeda/Ohio Diamond Style</i>	1
08-OS-040D		<i>/-- LOCATION: Curbside Wall, over the head of the S/B</i>	1
08-OS-0404		<i>/-- Oxygen Outlet No 4: Amico Console - Ohmeda/Ohio Diamond Style</i>	1
08-OS-040C		<i>/-- LOCATION: Center Pad of Liner Panel, Over Head/Chest</i>	1
08-OS-0905	<	<i>/-- Port Cyl Rack No 2: Zico QR-D-2 - D or Jumbo D - No Strap Req</i> Through bolt the rack to metal.	1
ZZ-ZZ-ZZ01	S	<i>/-- Rack Location : Aisle side of RF ALS cabinet</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
08-OS-090X	<	<i>/-- Port Cyl Rack No 1: Zico QR-D-2 - D or Jumbo D - No Strap Req</i> Through bolt the rack to metal.	1
08-OS-09L1	S	<i>/-- Rack Location : Aisle side of RF ALS cabinet</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
08-OS-1331	<	<i>/-- Rack No 1: Adjustable AEV O2 Rack Green with 4 Ratchet Straps M/H</i> Fits cylinders 7" diameter or more.	1
08-OS-11G1	<	<i>/-- Cylinder Type: OXYGEN - Green Colored Hose</i> Regulator connection Nut: 9/16" RH thread.	1
08-OS-1301		<i>/-- Rack Location: Left Front, wall #2 near wall #3</i>	1
08-OS-132M		<i>/-- Set up For M cylinder</i>	1
08-OS-1712	<	<i>/-- Regulator, Oxygen: Has LX1 Transducer, Inspected and Installed</i> Installed on O2 line for pressure test, Regulator and Transducer connected and left installed on Oxygen hose. Tagged with Inspector signature/Date Protected for shipment and left on the hose, Plastic restraint tie to the oxygen bracket for shipment > Required under Change notice 11, July 1, 2018 .	1
08-OS-1902		<i>/-- Regulator Wrench: Cast aluminum, OXYGEN w/ cable lanyard</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
08-OS-1400	<	<i>/-- Electric Oxygen, 12V solenoid valve w/ manual by-pass</i> Location: In Action Area	1
08-OS-35ST		<i>/-- Vacuum System: SSCOR regulator/gauge panel in A/A</i>	1
08-OS-3512	<	<i>/-- Collection Canister w Clip Bemis, 1200 CC Capacity In pull out drawer</i> <b>below AA</b> Location: Recessed under the action area. Install slides, cannister rides on a tray. Install lexan face with a notch for hose to pass through The lexan. Cannister installs on the tray with SSCOR canister retention clip	1
08-OS-3502		<i>/-- VAC Plumbing: Direct from panel to canister - NO Outlet</i>	1
08-OS-3503		<i>/-- Vacuum Pump: 49 State</i>	1
08-OS-35L8		<i>/-- Location: M-1a Compartment</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
ZZ-ZZ-ZZZZ		<i>/--</i>	1
08-ZZ-ZZZZ			1
<b>TRIM / DOOR ASSEMBLY - CELL 5</b>			1
09-00-002S		<i>/-- Interior window and aluminum trim with standard satin finish- std</i>	1
09-00-0001			1
09-00-000Z		*****Door Department X Series > New	1
02-BT-C85V		<i>/-- Handles, Ext: Tri-mark 1875, Free Float, Polished CNNC finish X-Series</i>	1

PART NO	S	DESCRIPTION	QTY
02-BT-C85A	<	<b>/-- Interior Release: All Entry Doors, with bezel Emergency Access</b> All three Entry Doors, top and bottom latches. Bezel installed around emergency release.	1
09-B1-ED0X		/-- Entry Door Panels, Windows and Hardware, X-Series Units	1
08-MH-0020		<b>/-- Interior Grab Handle Color: Yellow Antimicrobial</b>	1
08-MH-03B6		<b>/-- Grab Handle, CS Entry: 1 1/4" Dia..... S/S, 2-pt 18"L, Yellow Antimicrobial</b>	1
08-MH-03D6		<b>/-- Grab Handles, Rear Access: (2) 12"L X 1 1/4" Dia..... S/S, 2-pt, Yellow</b>	1
		<b>Antimicr</b>	
09-MH-2520	S <	<b>/-- Grab Rail, (1), 18" IATS, Yellow Antimicrobial</b> <b>Located : Rear Street Side Wall</b>	1
09-AS-2402	S	<b>/-- Door Panels: Mica / Stainless / Smooth Aluminum</b>	1
09-AS-2535		<b>/-- Curbside Lower Door Panel: Smooth Aluminum</b>	1
09-WI-02BX		/-- "AUTO SHADE" Windows: Upper R/A Doors, Fixed Glass, X-Series STD	1
09-WI-06BX		/-- "AUTO SHADE" Window: Upper C/S Access, Fixed Glass, X-Series STD	1
09-WI-09BX	<	<b>/-- Inverter, "Auto Shade" Windows : Part of X series windows</b> part MDUL-WINDOW	1
09-IN-3STX	<	/-- Insulation: All Module Doors, 2" Black Foam, X-Series units #INSU-ARM2	1
09-IN-3STY	<	/-- Insulation: All Module Doors, Black Sound Proofing, X-Series units #INSU-KSU	1
09-MH-2531	<	<b>/-- Grab Rail, (1), 18" Yellow Antimicrobial Rear Entry Assist std.</b> Located : Module interior at the rear entry, mounted to the M5 compartment filler. Rail is to be through bolted into M5.	1
09-DR-WT00		Talk Through Window: Sliding Lexan Window - CLEAR	1
09-DR-WT20		/-- Sliding Window Locking Pin: 1/4" with Lanyard	1
09-FM-10X3		<b>Dri-Dek Compt Floors and shelves, Black, STD X-Series</b>	1
09-FM-11X7		<b>/-- Dri-Dek EDGES: Yellow, Beveled frontal edges</b>	1
ZZ-ZZ-ZZZZ		<b>/--</b>	1
07-WC-LPM5	<	<b>/-- Defibrillator Bracket: Ferno D360 Surface, swivel Zoll X Series Defibrillator,</b> Model #082 2432 SAE Compliant to J3043 testing by vendor.	1
07-WC-LPTS	S <	<b>/-- Monitor Mounting: Bolted in place</b> <b>Location:TO BE DETERMINED AT DELIVERY</b>	1
07-ZZ-ZZZZ		<b>/--</b>	1
07-ZZ-ZZZZ		<b>/--</b>	1
		<b>ELECTRICAL Point to Point - CELL 6</b>	1
06-EC-1400		<b>/-- IV Warmer No 1: Smithworks, 12VDC, FloorMount (Tray style)</b>	1
06-EC-1410	S	<b>/-- Location: Drawer I-2A</b>	1
10-MC-0105		<b>/-- Knox Box Medvault: Install Customer Supplied Knox Box</b>	1
06-EC-1418	S	<b>/-- Location: I-2 of RF ALS</b>	1
ZZ-ZZ-ZZZZ		<b>/--</b>	1
10-MC-0105	X <	<b>/-- Knox Key Secure Box: Install Customer Supplied Knox Key Secure Box</b> <b>LOCATION: In Cab Between Cab Seats on Back Wall (Reference 18OF 23541XA)</b>	1
10-EB-13X2		Cabinet Light(s) : "DAY BRIGHT" LED White Lights, X-Series Units	1
05-IL-13S1		/-- Cab Interior Lights Switching: Thru MultiPlex System	1
10-EB-13Y0		/-- Daybright location 1	1
10-EB-13YE		<b>/-- Daybright Light Location Cabinet B-1</b>	1
10-EB-13Y1		/-- Daybright location 2	1
10-EB-13YB	S	<b>/-- Daybright Light Location Cabinet B-2</b>	1
10-EB-13Y2		/-- Daybright location 3	1
10-EB-13Y0	S	<b>/-- Daybright Light Location Cabinet K1</b>	1
10-EB-13Y3		/-- Daybright location 4	1
10-EB-13YC	S	<b>/-- Daybright Light Location Cabinet K2</b>	1
10-EB-13Y4		/-- Daybright location 5	1
10-EB-13YG		<b>/-- Daybright Light Location Cabinet G</b>	1

PART NO	S	DESCRIPTION	QTY
10-EB-13Y5		-- Daybright location 6	1
<b>10-EB-13YC</b>		-- <b>Daybright Light Location Cabinet C</b>	1
10-EB-13Y6		-- Daybright location 7	1
<b>10-EB-13YA</b>		-- <b>Daybright Light Location Cabinet A</b>	1
10-IL-02ST		Action Area Light: 12V, LED, Surface Mount	1
10-IL-02L7		-- Light Location: Action Area	1
<b>UPHOLSTERY - CELL 7</b>			1
<b>11-00-0001</b>	<b>S</b>	<b>&lt; Full Length Squad Bench Pad</b>	1
<b>NOTE: Install Pad On Squad Bench Surface Above Sharps/Trash Drawer Also</b>			
<b>11-00-UC04</b>		<b>Upholstery Color: Light Gray( Dove) Vac form</b>	1
<b>11-00-UC11</b>		<b> -- Center Trough Upholstery Color: Color Key to Rest of Truck</b>	1
<b>ZZ-ZZ-ZZZZ</b>		--	1
11-00-UT0X		Uph Joint Type: "PREMIUM " Upgrade	1
11-SB-0005		Squad Bench seat cushion cut-outs: None	1
11-SB-0003		-- Post And Wheel Cups: NONE	1
11-SE-CSPD		Head Protection: Pad over CS Entry Door	1
11-SE-REPD		Head Protection: 2" Pad over Rear Access Doors, Full Width	1
<b>11-MC-1700</b>		<b> -- Clock: Intellitec Digital / Sweep Emergency Time Manager</b>	1
<b>11-MC-1900</b>	<b>S</b>	<b> -- Location: M-5 Filler Facing Front of Truck</b>	1
<b>PAINT - STRIPES - DECALS</b>			1
12-PT-UNCT		-- Undercoating : Per QVM Guidelines, STD	1
12-DC-0001		Reflective Tape: On painted edges of Exterior Door Frame	1
12-DC-GA10		Compartment Finish: Diamond Plate Standard	1
12-PT-0100		Primary (Over All) Color: White (YZ)	1
<b>12-00-0001</b>	<b>S</b>	<b> -- CUSTOM QUOTE FULL CHEVRONS/GRAPHICS</b>	1
12-DC-0002	<b>&lt;</b>	-- Flip Step Reflective/Prismatic Tape: Red/White/R/W/R/W/R	1
Install on rearward facing edge of flip up step at rear module entry.			
<b>12-PT-0122</b>	<b>S</b>	<b>&lt;  -- Tape Belt Stripe: Reflective Tape</b>	1
Install 12" Tape Belt.			
Install Kickup.			
Install 1.5" Tape Belt.			
1.5" Black Reflective Tape Belt			
.5"Gap			
12" Red Reflective Tape Belt with kickup			
.5" Gap			
1.5" Black Reflective Tape Belt			
3/8" Black Reflective Double Vinyl Pinstripe on Red Reflective Tape Belt.			
<b>12-PT-0601</b>		<b> -- Belt **NOT** Across Hood</b>	1
<b>ZZ-ZZ-ZZZZ</b>		--	1
12-PT-0600		-- Paint Belt: NONE	1
<b>12-PT-1000</b>	<b>S</b>	<b> -- Pin Stripe: 3/8" Double Vinyl Pinstripe</b>	1
<b>12-ZZ-ZZZZ</b>	<b>S</b>	<b> -- Window Perf with Gold Stars of Life</b>	1
<b>12-PT-RF01</b>	<b>&lt;</b>	<b> -- Roof Paint: Color and finish quality to be GLOSSY</b>	1
The roof shall be painted, with a glossy finish, but not sanded and buffed.			
<b>ZZ-ZZ-ZZZZ</b>		--	1
12-PT-1000		Pin Stripe: NONE	1
<b>12-ZZ-ZZZZ</b>		--	1
<b>12-PT-1314</b>		<b> -- Outer Section: including doors</b>	1
<b>12-PT-1328</b>	<b>S</b>	<b>&lt;  -- Full Rear Chevron, includes doors Diamond Grade Reflective: Double Color</b>	1
See Below for Colors			
<b>12-PT-1380</b>	<b>S</b>	<b> -- Main Color - Red Diamond Grade</b>	1
<b>12-PT-1382</b>	<b>S</b>	<b> -- Second Color - Yellow Diamond Grade</b>	1
<b>12-PT-1332</b>	<b>S</b>	<b> -- Rear Kickplate Diamond Grade Reflective: Double Color</b>	1
<b>12-PT-1336</b>	<b>S</b>	<b> -- Rear Kickplate Double Color - To make two color Chevron</b>	1
<b>12-PT-1380</b>	<b>S</b>	<b> -- Main Color - Red Diamond Grade</b>	1
<b>12-PT-1382</b>	<b>S</b>	<b> -- Second Color - Yellow Diamond Grade</b>	1
<b>12-PT-135B</b>	<b>S</b>	<b>&lt;  -- Inside of (3) Entry Doors: Lower Panels, Double Colors Diamond Grade</b>	1
Reflective			
State Colors Required			
1st color : Red Diamond Grade			



PART NO	S	DESCRIPTION	QTY
		2nd color : Yellow Diamond Grade	
12-PT-2000	S	< <b>Lettering: Oak Park FD Design (Reference 18OF 23541XA)</b>	1
		---StreetSide---	
		5.6" "OAK PARK" arched, Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		11.4" SOL, Inkjet Reflective & Gold Engine Turn with Black outline	
		4" "FIRE DEPARTMENT", Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		2.5" "PARAMEDIC UNIT" Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		2.3" "EMERGENCY CALL 911" Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		---CurbSide---	
		5.6" "OAK PARK" arched, Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		11.4" SOL, Inkjet Reflective & Gold Engine Turn with Black outline	
		4" "FIRE DEPARTMENT", Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		2.5" "PARAMEDIC UNIT" Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		2.3" "EMERGENCY CALL 911" Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		---Front---	
		5.17" "OAK PARK" Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		---Rear---	
		2 - 8.5" SOL, Inkjet Reflective & Gold Engine Turn with Black outline	
		4.16" "OAK PARAMEDIC" Inkjet Reflective & Gold Engine Turn with Black oblique projection	
		4.16" "PARK UNIT" Inkjet Reflective & Gold Engine Turn with Black oblique projection	
12-ZZ-ZZZZ		--	1
12-PT-DRIP		< Drip Rails: Bright Aluminum, De-burred and rounded corners Include a drip rail over the C/S Entry Door.	1
12-ZZ-ZZZZ			1
		<b>DETAIL - SHIP LOOSE ITEMS</b>	1
12-PT-DRIZ		<  -- Drip Rails: Detail-Refer to Paint Section for Drip Rail Information Include a drip rail over the C/S Entry Door.	1
13-00-0200		-- *Check front of W/O under chassis section for Add' items*	1
ZZ-ZZ-ZZZZ		--	1
13-10-XM00		-- Owner's Manual USB Flash Drive ship loose	1
13-10-XMA0		-- Printed Owner's Manual Not Required	1
13-00-0001			1
13-GL-0000		Glove Holder, Ship Loose: NONE	1
ZZ-ZZ-ZZZZ		--	1
13-KK-KDEC		Decals: KKK / DOT Pkg, Blue/White reflective - Ship Loose	1
13-RF-STAR		-- <b>Decals: Install 32" Star of Life on Mod Roof</b>	1
ZZ-ZZ-ZZZZ		--	1
13-KK-NSSB		Decals: NO SMOKING & SEATBELT, installed, cab & pt. area.	1
ZZ-ZZ-ZZZZ		--	1
13-KL-0010		AEV Logos: Installed on unit per AEV standard locations	1
13-MH-05ST		< <b>Fire Extinguisher, 5 pound, shipped loose, Std</b> Part No: EXTI-01	1
11-YZ-0932		<  -- Exception to 3.15.2 Required Two fire extinguishers installed by FSAM Fire extinguishers were not installed with one in the driver's cab, one in the patient compartment at the time of departure from the final stage Ambulance Manufacturer. The customer/FSAM has shipped them loose for the dealer to complete the final install.	1



PART NO	S	DESCRIPTION	QTY
11-ZZ-0932	<	-- Exception to C.16.1 1 Required Two fire extinguishers installed by FSAM Fire extinguishers were not installed iwth one in the driver's cab, one in the patient compartment at the time of departure from the final stage Ambulance Manufacturer.	1
13-MH-10A0		Reflector Pkg: Body - 2ea, Side Fr Amber, Side Rear Red, Rear Red	1
ZZ-ZZ-ZZZZ	--		1
13-SB-0003		Post And Wheel Cups: NONE	1
13-SP-TIRE		Spare Tire: Refer To Chassis Section to See if it gets one.	1
34-XX-0001		Primary Cot: NONE included	1
ZZ-ZZ-ZZZZ	--		1
34-XX-0002		Secondary Stretcher: NONE included	1
ZZ-ZZ-ZZZZ	--		1
34-XX-5000	<	Indemnification Statement The purchaser agrees to defend, indemnify and hold REV harmless from any claims, costs (including actual attorneys' fees), damages and liabilities caused in whole or in part by any alteration or modification of, or changes or additions to the Purchased Products OR use of product for purposes it was not designed or intended for.	1
		<b>== 172 x 96 T-1 LWB Ford X Base Price - 15.015 03/09/20 ==</b>	1
		<b>GENERAL CONVERSION</b>	1
<b>03-07-003H</b>	<b>S</b>	<b>2020 **172*** F-550 4 x 4 (X-Series ) Gas Conv PKG - 20-1</b>	1
<b>03-07-3000</b>	<	<b> -- Module Body Delivery surcharge</b> <b>Effective March 9th on new orders created.</b>	1
36-AA-0001		WORK ORDER STATUS:	1
00-90-0301	--	For Confirmation	1
36-CO-0001	--	CHANGE ORDER POLICY	1
36-CO-0010	<	-- After Confirmation, Prior to Engineering Change Fee is \$50 Per Item, Plus Option Cost	1
36-CO-0020	<	-- After Confirmation, After Engineering Start Change Fee is \$100 Per Item, Plus 150% Option Cost  Special order or non-stocking parts that are purchased for any ordered option that is subsequently deleted will be charged for and shipped loose.	1
36-CO-0030	<	-- After Confirmation, After Production Start Change Fee is \$100 Per Item, Plus 200% Option Cost  Special order or non-stocking parts that are purchased for any ordered option that is subsequently deleted will be charged for and shipped loose.	1
ZZ-ZZ-ZZZZ	--		1
36-EO-0001	--	***END OF ORDER***	1